

1.3 Megapixel WDR Fixed Pinhole Bullet

Model: VSIP1MPPH



This wide-dynamic IP pinhole camera is designed for discreet/covert surveillance applications and is ideal for use at controlled ingress points, in shelf surveillance, in-vehicles, ATMs and more.

Camera Features


- Stream up to 1.3 megapixel (1280 x 960) at 25fps
- 3.7mm fixed lens with 77° viewing angle
- Day/night (electronic), 3D noise reduction & auto white balance
- Wide dynamic range (100dB) with back/highlight compensation
- Discreet pinhole profile: 12mm diameter / 5mm depth
- Smart detection support incl. face detection and scene change
- MicroSD card slot for at-the-edge recording, up to 64GB
- Power via 12VDC or Power over Ethernet (802.3af)
- IP66 and IK10 rated housing for external use
- ONVIF, PSIA and CGI compliance

Compatible Accessories

This camera features an image sensor/lens separated by an 8m cable connected to a control unit and is connected via USB port. The VSIP1MPPH comes standard with:

- 1 x Adhesive-fastened flush mount bracket for pinhole mounting
- 1 x Screw-on clamp to secure pinhole camera
- 1 x Mounting kit for control unit with wall-plugs & screws

Model		VSIP1MPPH
General		
Camera Style	Pinhole Bullet	
Image Sensor	1/3" 1.3 Megapixel Progressive Scan CMOS	
Effective Pixels	1280 (H) x 960 (V)	
Signal Noise Ratio	> 50dB	
Camera		
Lens	3.7mm F2.8 Fixed Lens	
Angle of View	77°	
Electronic Shutter	Auto/Manual, 1/3 ~ 1/10000s	
Minimum Illumination	0.01 Lux at F2.8 (Colour) / 0.001 Lux at F2.8 (B&W)	
Day/Night	Auto (electronic) / Colour / B&W	
White Balance	Auto / Manual	
Noise Reduction	3D Digital Noise Reduction	
Gain Control	Auto / Manual	
Backlight Compensation	BLC / HLC / WDR (100dB)	
Audio Input	1 ch. Input / 1ch. Output	
Audio Compression	G.711a / G.711u / PCM	
Alarm Interface	1 ch. input / 1 ch. output	
Network Interface	RJ45 (10/100/1000 Base-T)	
Memory Slot	MicroSD slot up to 64GB	
Bit Rate	H.264: 48K ~ 8192Kbps	
ONVIF Conformance	ONVIF, PSIA, CGI Compliant	
Smart Functions	Tripwire / Intrusion / Scene Change / Face Detection	
Video		
Video Compression	H.264 / MJPEG	
Resolution	Configurable from 1.3MP (1280 x 960) to CIF (352 x 288)	
Frame Rate	Main	1.3MP and lower (1 ~ 25fps)
	Sub	D1 and lower (1 ~ 25fps)
	Third	N/A
Video Output	N/A	
Environment		
Ingress Protection	N/A	
Vandal Resistant	N/A	
Maximum Infrared Range	N/A	
Power Input	12VDC / PoE (802.3af)	
Power Consumption	< 7W	
Dimensions	110 x 83 x 24mm	
Weight	0.46kg	
Operating Environment	-30° to 60°C / RH95% (max)	
Product Dimensions		



Your local VIP Vision™ professional: