

# IP PTZ Control Keyboard

VSIPPTZKBV2



Specifications - PTZ Control Equipment		
System	Direct Interface	RS232/RS485
	Display	75.2mm x 33.85mm LCD
Design	Joystick	3-axis, vector-solving, with twisting, return to-center head
Network	Network Interface	RJ45
General	Operating Temperature	-10 ~ +55°C / 10 ~ 90%RH (max.)
	Atmosphere Pressure	86kpa~106kpa
	Power Supply	Input 100V~240V 50Hz / 60Hz, Output DC12V/1000mA
	Power Consumption	5W
	Dimensions	330 x 160 x 37.5mm
	Weight	2.5kg
	Warranty (Years)	4

## Product Overview

The IP PTZ control keyboard is compatible with all VIP Vision, Securview and Watchguard PTZ cameras over a network.

- Control a variety of PTZ cameras and DVRs with this PTZ keyboard
- Features RS485, RS422, USB, RS232 & RJ45 connections
- Three dimensional joystick control of PTZ functions
- Preset position, auto scan, auto pan, auto tour & pattern control
- 3.2" on-keyboard LCD with user menu and operation/procedure tips
- Interfaces to PTZ domes and DVR/NVR via Network mode and Direct mode
- Network mode: Control via RJ45 using IP address and ports
- Direct mode: Control via RS232/RS485 w/ protocols below
- DVR: DH2 / Camera protocols: DH-SD, PELCO-D/-P/-D1/-P1
- Can connect and control via VIP Vision SmartPSS through USB

