



## Linkable LED Strip Lighting

Available in 13W in two colour temperatures, with surface & right angle brackets

The ENSA™ LED linkable strip light range offers energy efficient lighting in a uniquely versatile, slim package. Connect three LED strip lights together for a maximum 3.5m length LED light strip.

Each linkable strip light comes standard with light connectors, connector safety caps, and surface mount and right angle mount clips. The simple mounting clips enable implementation of the linkable strip light across a wide variety of applications including shelf and cabinet lighting, accent lighting, recessed wall-wash lighting and more.

- Unique, energy efficient linkable LED strip lighting.
- Connect up to 3 lights together; easy on/off switch.
- 78lm/W luminous efficacy & 30,000 hours service life.
- Available in 3000K warm white and 6500K cool white.
- Right angle & surface clips enable rapid light installation.
- Wide 135° beam angle and >80 colour rendering index.

## Series Specifications

<b>Model</b>	<b>LEDBR13W</b>	
<b>Product Image</b>		
<b>Series Name</b>		
<b>Optical</b>		
<b>Luminous Flux</b>	1050lm	
<b>Luminous Efficacy</b>	78lm/W	
<b>Colour Temperature</b>	3000K / 6500K	
<b>Colour Rendering Index</b>	> 80	
<b>Beam Angle</b>	135°	
<b>Light Decay</b>	<10% after 6,000 hours	
<b>Rated Lifespan</b>	> 30,000 hours	
<b>Electrical</b>		
<b>Power Consumption</b>	13.5W	
<b>Input Voltage</b>	220 ~ 240VAC (50 ~ 60Hz)	
<b>Power Factor</b>	> 0.5	
<b>Dimmable</b>	N/A	
<b>General</b>		
<b>Plug / Socket / Base</b>	3-pin AC plug	
<b>Reflector / Diffuser</b>	Frosted diffuser	
<b>Housing Construction</b>	Polycarbonate & aluminium	
<b>Operating Environment</b>	-25° ~ +40°C	
<b>Dimensions</b>	1170 x 25 x 35mm	
<b>Equivalent Wattage</b>	50W halogen	

<b>Photometry</b>														
<b>Illuminance at a Distance</b>	<table border="1"> <thead> <tr> <th>Centre Beam Avg (lx)</th> <th>Beam Diameter (m)</th> </tr> </thead> <tbody> <tr> <td>0.5m: 257</td> <td>1.73</td> </tr> <tr> <td>1.0m: 64</td> <td>3.46</td> </tr> <tr> <td>1.5m: 29</td> <td>5.19</td> </tr> <tr> <td>2.0m: 16</td> <td>6.93</td> </tr> <tr> <td>2.5m: 10</td> <td>10.39</td> </tr> </tbody> </table>	Centre Beam Avg (lx)	Beam Diameter (m)	0.5m: 257	1.73	1.0m: 64	3.46	1.5m: 29	5.19	2.0m: 16	6.93	2.5m: 10	10.39	
Centre Beam Avg (lx)	Beam Diameter (m)													
0.5m: 257	1.73													
1.0m: 64	3.46													
1.5m: 29	5.19													
2.0m: 16	6.93													
2.5m: 10	10.39													

<b>Diagrams</b>	
<b>Mounting Options</b>	

## Ordering Information

Type	Wattage	Colour Temperature
LEDBR	13W (13.5W)	3K (Warm white) 65K (Cool white)

**LEDBR13W65K: 13W LED Linkable Strip Light in Cool White**