



Built for road performance.

Mobile Series: Full HD 1080p HDCVI mobile surveillance cameras in 2.0MP

Keep every angle of your vehicle covered with Mobile Series surveillance cameras from Securview. Choose from vandal dome, compact dome & bumper cameras, capable of Full HD streaming in durable IP67 rated housings.

- Stream 2.0MP / Full HD 1080p (1920 x 1080) 25fps
- Fixed lens, available in 111° to 83° viewing angles
- Smart infrared illumination, up to 20m range
- Built-in microphone mobile series models available
- IP67 weather resistant metal housings (all models)
- Shock resistant housings with aviation connectors
- DIRFT dome: Low profile & IK10 vandal resistant
- DIRAT dome: Smaller than a tennis ball Ø62 x 62mm
- CIRAT camera: Ideal for bumper placement
- BT camera: Ideal for flush mount in-bumper



Built-in Mic Models Available



20m Infrared and low light vision



IP67 Rated Across the Range

Model		VSCVI2MPVDIRFTV3	VSCVI2MPDIRAT	VSCVI2MPCIRAT	VSCVI2MPBT2.8
General	Product Image				
	Camera Style	Mobile Wedge Dome	Mobile Dome Camera	Mobile Bumper Camera	Mobile Bullet Camera
	Image Sensor	1/2.8" 2.1 Megapixel CMOS		1/2.9" 2.0 Megapixel CMOS	
	Effective Pixels	1920(H)x1080(V)		1920 (H) x 1080 (V)	
	Signal Noise Ratio	> 65dB			
Camera	Lens	3.6mm F1.6 Fixed Lens	3.6mm F2.0 Fixed Lens	3.6mm F2.0 Fixed Lens	2.8mm F2.0 Fixed Lens
	Angle of View	110°	83°	83°	109°
	Focus	Fixed	Fixed / 0.8m Min. Focus Distance	Fixed / 0.8m Min. Focus Distance	Fixed / 0.5m Min. Focus Distance
	Minimum Illumination	0.005 Lux at F1.6 (Colour) / 0 Lux IR Active	0.02 Lux at F2.0 (Colour) / 0 Lux IR Active	0.02 Lux at F2.0 (Colour) / 0 Lux IR Active	0.02 Lux F2.0 (Colour) / 0.002 Lux (B/W)
	Electronic Shutter	1/4 ~ 1/100,000s	1/25 ~ 1/100,000s		
	Day/Night	Auto (ICR) / Manual			
	Infrared Range	20m	20m	20m	N/A
	White Balance	Auto / Manual			
	Noise Reduction	2D / 3D	2D		
	Gain Control	Auto			
	Lighting Compensation	BLC / HLC / WDR (120dB)	BLC / HLC / DWDR		
Video	Resolution	1080p (1920 x 1080) to CIF (352 x 288)			
	Frame Rate	25fps (1080p and lower)			
	Transmission Distance	3m / 6m / 12m / 18m heavy duty cables available			
DORI	Detect	55m	57m	57m	40m
	Observe	22m	23m	23m	16m
	Recognise	11m	11m	11m	8m
	Identify	6m	9m	6m	4m
Interface	Audio Input	N/A	Built-in microphone	Built-in microphone	N/A
	Alarm Interface	N/A			
	Video Output	1x BNC HDCVI output			
	OSD Menu	Support			
Environmental	Ingress Protection	IP67			N/A
	Vandal Resistant	IK10	N/A		Metal
	Housing	Metal, Polycarbonate	Metal		
	Power Input	12VDC			
	Power Consumption	<3.6W	<2.9W	<2.9W	<0.6W
	Dimensions	Ø106 x 50mm	Ø62 x 62mm	107 x 43 x 55mm	Ø30 x 68mm
	Weight	0.31kg	0.16kg	0.31kg	0.07kg
Operating Environment	-40° to 60°C / RH90% (max)		-40° to 70°C / RH90% (max)		
Accessories	Product Diagram				

Your local Securview™ HDCVI solutions professional: