1.3 Megapixel Infrared Fixed Mini Bullet

Model: VSIP1MPFBIRV4





Taking standard IP surveillance cameras to the next level with improved infrared capability, triple stream encoding and smart detection features such as face detection.

Camera Features

- Stream up to 1.3 megapixel (1280 x 960) at 25fps
- 3.6mm fixed lens with 74° viewing angle
- Day/night (auto ICR) with 40m maximum infrared range
- · Back/highlight compensation with digital wide dynamic range
- 3D digital noise reduction and auto white balance
- Power via 12VDC or Power over Ethernet (802.3af)
- Supports triple stream and smart detection technology
- IP67 weather resistant housing for external use
- ONVIF, PSIA and CGI compliance

Compatible Accessories

Accessories sold separately, adapters may be required.








VSBKTA121

VSBKTA152

VSBKTA151

Model		VSIP1MPFBIRV4
General		
Camera Style		Weather Resistant Mini Bullet
Image Sensor		1/3" 1.3 Megapixel Progressive Scan CMOS
Effective Pixels		1280 (H) x 960 (V)
Signal Noise Ratio		> 50dB
Camera		
Lens		3.6mm F2.2 Fixed Lens
Angle of View		74°
Electronic Shutter		Auto / Manual (1/3 ~ 1/100000s)
Minimum Illumination		0.01 Lux at F2.2 (Colour) / 0 Lux at F2.2 (IR on)
Day/Night		Auto (ICR) / Colour / B&W
White Balance		Auto / Manual
Noise Reduction		3D Digital Noise Reduction
Gain Control		Auto / Manual
Backlight Compensation		BLC / HLC / DWDR
Audio Input		N/A
Audio Compression		N/A
Alarm Interface		N/A
Network Interface		RJ45 (10/100 Base-T)
Memory Slot		N/A
Bit Rate		H.264: 32K ~ 10Mbps
ONVIF Conformance		ONVIF, PSIA, CGI Compliant
Smart Functions		Tripwire / Intrusion / Scene Change / Face Detection
Video		
Video Compression		H.264 / H.264B / H.264H / MJPEG
Resolution		Configurable from 1.3MP (1280 x 960) to CIF (352 x 288)
Frame Rate	Main	1.3MP and lower (1 ~ 25fps)
	Sub	D1 and lower (1 ~ 25fps)
	Third	720p and lower (1 ~ 14fps)
Video Output		N/A
Environment		
Ingress Protection		IP67
Vandal Resistant		N/A
Maximum Infrared Range		40m
Power Input		12VDC / PoE (802.3af)
Power Consumption		< 5.5W
Dimensions		70 x 70 x 180mm
Weight		0.40kg
Operating Environment		-40° to 60°C / RH95% (max)
Product Dime	nsions	





Your local VIP Vision™ professional: