## 2.0 Megapixel IP Mobile PTZ IP Camera

Model: VSIP2MPPTZIRM





Purpose built to be integrated into large vehicles such as earth moving equipment, the mobility of the VIP Vision Mobile PTZ offers a truly versatile vehicle surveillance experience.

## **Camera Features**

- Stream up to 2.0 megapixel (1920 x 1080) at 25fps
- 5.5 ~ 110mm 20x optical zoom lens with 51 ~ 2.6° viewing angles
- Versatile power supply: compatible with 8 ~ 36VDC vehicles
- Features up to 150m maximum infrared distance & lens wiper
- Day/night (auto ICR) with back/highlight compensation
- Durable, IP66 rated all-metal aluminium alloy construction
- Endless 360° panning with ultra-versatile -90 ~ 90° tilt adjust
- · Configure PTZ patterns, tours and auto-scanning
- 6000V anti-lightning surge protection
- ONVIF profile S compliant

## **Compatible Products**

Compatible items sold separately.






MNVR-GPS

VSWAN4G

Model		VSIP2MPPTZIRM
General		
Camera Style		Weather Resistant Mobile Positioning System
Image Sensor		1/2.8" 2.0 Megapixel Progressive Scan Exmor CMOS
Effective Pixels		1944 (H) x 1092 (V)
Signal Noise Ratio		> 50dB
Camera		
Lens		5.5 ~ 110mm F1.6 ~ F3.5 Motorised Lens
Angle of View		51° (wide) ~ 2.6° (tele)
Electronic Shutter		Auto / Manual (1/1 ~ 1/30000s)
Minimum Illumination		0.05 Lux at F1.6 (Colour) / 0.005 Lux at F1.6 (B&W)
Day/Night		Auto (ICR) / Colour / B&W
White Balance		Auto / Manual / ATW / Indoor / Outdoor
Noise Reduction		2D / 3D Digital Noise Reduction
Gain Control		Auto / Manual
<b>Backlight Compensation</b>		BLC / HLC / DWDR
Audio Input		N/A
Audio Compression		N/A
Alarm Interface		N/A
Network Interface		RJ45 (10/100 Base-T)
Memory Slot		N/A
Bit Rate		H.264: 56K ~ 8192Kbps
ONVIF Conformance		Profile S Compliant
Smart Functions		N/A
Video		
Video Compression		H.264 / MJPEG
Resolution		Configurable from 2.0MP (1920 x 1080) to CIF (352 x 288)
Frame Rate	Main	1080p and lower (1 ~ 25fps)
	Sub	D1 and lower (1 ~ 25fps)
	Third	N/A
Video Output		N/A
PTZ		
Pan / Tilt Range		Pan: 0 ~ 360° (endless) / Tilt: -90 ~ 90°
Preset Speed		Pan: 60°/s; Tilt: 30°/s
Manual Speed		Pan: 60°/s; Tilt: 30°/s
PTZ Mode		4 Pattern, 4 Tour, Auto Scan
Presets		Up to 256
Speed Setup		Human oriented speed & focal length adaptation
Start-up Action		Auto-restore to previous PTZ/lens status
Environment		
Ingress Protection		
Vandal Resistant		IP66
	nt	N/A
Maximum Infra	nt	N/A 150m
Maximum Infra Power Input	nt ared Range	N/A 150m 8 ~ 36VDC
Maximum Infra Power Input Power Consum	nt ared Range	N/A 150m 8 ~ 36VDC < 60W
Maximum Infra Power Input Power Consum Dimensions	nt ared Range	N/A 150m 8 ~ 36VDC < 60W 375 x 246 x 210mm
Maximum Infra Power Input Power Consum	nt ared Range aption	N/A 150m 8 ~ 36VDC < 60W



Your local VIP Vision™ professional:

## **Full HD Mobile IP Surveillance in Action**



Features VSIP2MPPTZIRM mobile PTZ camera, MNVR-GPS mobile network video recorder with GPS and the VSWAN4G 3G/4G WiFi router.













Your local VIP Vision™ professional: