

All-in-one CCTV solutions.

Professional Series: 6.0MP Surveillance Kits available with 4, 8 & 16 cameras

VIP Vision™ Professional Series CCTV kits offer broadcast-quality image performance with built-in PoE for fast installations. Plus, the Pro AI turret cameras feature intelligent perimeter protection that identifies people & vehicles.

- Records 6.0MP (3072 x 1728) up to 20fps
- 6.0MP True WDR 50m IR turret cameras in 2.8mm
- IVS with tripwire, intrusion, motion detection & more
- Perimeter Protection to identify people & vehicles
- Remote view in seconds with setup via QR code
- HDMI & VGA simultaneous video output
- Built-in Power over Ethernet (ePoE for 8/16 channel)
- Pre-installed 1TB/2TB/4TB surveillance grade HDD(s)
- Remote view for iOS, Android & Windows Phone
 *Camera cabling sold separately







Comprehensive Remote View



Choose from three comprehensive, ready to install packages.

4 Channel

-P462F

4 Channel Professional NVR

- 4 port Power over Ethernet NVR
- Records 6.0MP at 20fps
- Pre-installed 1TB hard disk drive
 (additional backup via USB device or network)

4 x 6.0MP Pro Al Cameras

- 4 x Pro AI series turret dome cameras
- + 2.8mm (99°H / 53°V) fixed lens
- Stream up to 6.0MP (3072 x 1728)
- IP67 rated metal housing for outdoor use

Accessories

- CAT5 patch cable for networking: 1 x 1.5m
- HDMI output cable: 1 x 1m
- 1 x NVR Remote and 1 x Mouse
- · Camera cabling sold separately

8 Channel

KII-P864F

8 Channel Professional NVR

- 8 port Extended Power over Ethernet NVR
- · Records 6.0MP at 20fps
- Pre-installed 2TB hard disk drive (additional backup via USB device or network)

8 x 6.0MP Pro Al Cameras

- 8 x Pro Al series turret dome cameras
- 2.8mm (99°H / 53°V) fixed lens
 Stream up to 6.0MP (3072 x 1728)
- IP67 rated metal housing for outdoor use

Accessories

- CAT5 patch cable for networking: 1 x 1.5m
- HDMI output cable: 1 x 1m
- 1 x NVR Remote and 1 x Mouse
- · Camera cabling sold separately

6 Channel

KIT-P1668F

Product Image

16 Channel Professional NVR

- 16 port Extended Power over Ethernet NVR
 Records 6.0MP at 20fps
- Pre-installed 4TB hard disk drive
- (additional backup via USB device or network)

16 x 6.0MP Pro Al Cameras

- 16 x Pro Al series turret dome cameras
- 2.8mm (99°H / 53°V) fixed lens
- Stream up to 6.0MP (3072 x 1728)
- IP67 rated metal housing for outdoor use

Accessories

- CAT5 patch cable for networking: 1 x 1.5m
- HDMI output cable: 1 x 1m
- 1 x NVR Remote and 1 x Mouse
- · Camera cabling sold separately

Technical Specifications

For full specifications and bracket compatibility, please see the individual unit web entry or datasheet.

			er or	eroz
Video Input		4 channel	8 channel	16 channel
Two-way Talk		1 channel input / 1 channel output / RCA		1 channel input / 2 channel output / RCA
Video Output		1 x HDMI / 1 x VGA	1 x HDMI / 1 x VGA	2 x HDMI / 2 x VGA
Maximum Resolution		Configurable from 8.0MP (3840 x 2160) to CIF	Configurable from 12.0MP (4000 x 3000) to CIF (352 x 288)	
Incoming Bandwidth		200Mbps	320Mbps	
Video Compression		H.265 / H.264	H.265 / H.264 / MJPEG / MPEG4	
Bit Rate		16 ~ 20Mbps per channel		
Alarm Input / Output		4 channels input / 2 channels relay output	4 channels input / 2 channels relay output	16 channels input / 6 channels relay output
Internal HDD		2 x SATA ports, up to 10TB each (2TB pre-installed)	2 x SATA ports, up to 10TB each (4TB pre-installed)	4 x SATA ports, up to 10TB each (2 x 4TB pre-installed)
Power Supply		48VDC, 2A	100 ~ 240VAC, 50 ~ 60Hz	
Camera Model		VSIPP-6DIRG-I		
Product Image				
Image Sensor		1/2.7" 6.0MP Progressive Scan CMOS		
Lens		2.8mm Fixed Lens, Horizontal: 99°, Vertical: 53°		
Min. Illumination		0.005 Lux/F1.5 (Color)		
Infrared Range		2 x Infrared LED, 50m range, Auto/manual on/off control		
Lighting Compensation		BLC / HLC / WDR (120dB)		
Resolution		6.0MP (3072 x 1728) to CIF (352 x 288)		
Frame Rate	Main	6.0MP (1~20fps) / 4.0MP (1~25fps)		
	Sub	D1 (1 ~ 25fps)		
	Third	1080p (1 ~ 25fps)		
Audio Input		Built-in Microphone		
Smart Functions		Tripwire, Intrusion, Object Abandoned/Missing, Face Detection, Motion Detection (4 zones), Region of Interest (4 zones), Privacy Masking (4 zones), Smart Infrared		
Weather/Vandal Resist		IP67		
Power Input		12VDC / PoE (802.3af)		

Your local VIP Vision™ IP solutions professional: