Analogue to HD Upgrade.

4 Channel 720p HDCVI Complete Surveillance Kit

Model: CVR4PACK2

- 4 x 1.3 megapixel weatherproof bullets
- Pre-installed 1TB surveillance HDD
- Backup via USB device or local network
- Utilises HDCVI video transmission standard
- Record 720p (1280 x 720) at 25fps
- HDMI and VGA video outputs
- Remote view configuration via QR code
- · View on iOS, Android & Windows Phone devices

Experience your moment of victory[™]

720P

HD Video Over Coaxial Cable <u>Technology</u>

Upgrade from analogue to more than double your image resolution!

Experience your moment of victory:

- Upgrade your system
- Boost image resolution
- Capture fine detail
- Get usable evidence
- Enjoy peace of mind








4 Channel 720p HDCVI Complete Surveillance Kit

Model: CVR4PACK2





Embedded processo



Product Overview

The CVR4PACK2 is a 4 channel surveillance system capable of 720p HD recording over coax cable at 25fps. It features a compact DVR with HDMI and VGA outputs as well as a preinstalled 1TB surveillance hard drive. This DVR also has comprehensive remote view (iOS, Android & Windows Phone) and backup functionality (USB/ network).

The CVR4PACK2 is an ideal analogue to HD-video-overcoax upgrade package that enables you rapidly boost the image resolution of an existing analogue installation to high definition.

Victory Series products utilise the HDCVI video transmission standard, delivering video, audio and data across a single coaxial cable (RG59 / RG6 75-3 preferred). This also allows for up to 500m transmission distances for 720p HD video streams using standard coaxial cable (300m for 1080p video).

The CVR4PACK2 includes 4 weatherproof, 3.6mm fixed lens (70°), 20m infrared range, 1.3 megapixel cameras that are ideal for use in a multitude of applications. They can record at maximum resolution of 720p (1280 x 720), more than double the resolution when compared to traditional D1 analogue systems (720 x 576) and up to 9x greater versus CIF (352 x 288).

This kit does not include coaxial cable, splitters or camera power supplies. For new installs, one Victory Series accessory kit is required per 4 cameras (CVR4ACCPACK).



Upgrade to 1080p cameras for full HD recording. Max recording resolution: 1920 x 1080 at 12fps Model: CVR4PACK2F

PystemOperating SystemEmbedded Linux OSVideo Input4 channel BNCAudio Input4 channel RCAAudio Output1 channel RCAPreview Resolution1920 x 1080, 1280 x 1024, 1280 x 720, 1024 x 768, 800 x 600Display Split1/4OSDTitle, time, video loss, camera lock, motion detectionPreview Resolution1920 x 1080, 1280 x 1024, 1280 x 720, 1024 x 768, 800 x 600Display Split1/4OSDTitle, time, video loss, camera lock, motion detectionPreview Resolution1080p (1920 x 1080) / 720p (1280 x 720)Record RateMain: 1080p (1920 x 1080) / 720p (1280 x 720)Record RateMain: 1080p (1920 x 1080) / 720p (1280 x 720)Record RateMain: 1080p (1920 x 1080) / 720p (1280 x 720)Record RateMain: 1080p (1920 x 1080) / 720p (1280 x 720)Record RateMain: 1080p (1920 x 1080) / 720p (1280 x 720)Record RateMain: 1080p (1920 x 1080) / 720p (1280 x 720)Record RateMain: 1080p (1920 x 1080) / 720p (1280 x 720)Record RateMain: 1080p (1920 x 1080) / 720p (1280 x 720)Record RateMain: 1080p (1920 x 1080) / 720p (1280 x 720)Record RateNARecord NodesUSB Device / NetworkRecord RateNanual / Schedule (Regular [Continuous], MD) / StopMax. User Access128 usersRemote ViewiOS (iPhone, iPad); Android devices, Windows PhoneStorageInternal HDD1 SATA port / 1TB surveillance hard drive (installed)USB Interface2 ports (1 Rear), US82.0Resords<	System	Main Processor	Embedded processor
Video Input4 channel BNCAudio Input4 channel RCAAudio Output1 channel RCAAudio Output1 HDMI / 1 VGAPreview Resolution1920 x 1080, 1280 x 1024, 1280 x 720, 1024 x 768, 800 x 600Display Applit1 / 4OSDTitle, time, video loss, camera lock, motion detectionRecord Resolution1826 / G.711Record Resolution1080p (1920 x 1080) / 720p (1280 x 720)Record Resolution1080p (1920 x 1080) / 720p (1-25fps) / Sub: D1 (1~12fps)Record RateMain: 1080p (1~12fps), 720p (1~25fps) / Sub: D1 (1~12fps)Record ModesManual / Schedule (Regular [Continuous], MD) / StopBackup & NetworkEthernetR-45 port (10/100M)Max. User Access128 usersRemote ViewiOS (iPhone, iPad); Android devices, Windows PhoneStorageInternal HDD1 SATA port / 1TB surveillance hard drive (installed)USB Interface2 ports (1 Rear), USB2.0Res232N/ARes4851 port, for PTZ ControlPower SupplyDC12V/2AOperating Environment-10 ~+55°C / 10~90%RH / 86~106kpaDimensions325mm x 245mm x 45mm (Mini 1U)		Operating System	Embedded Linux OS
NumberAudio Output1 channel RCAVideo Output1 HDMI / 1 VGAPreview Resolution1920 x 1080, 1280 x 1024, 1280 x 720, 1024 x 768, 800 x 600Display Split1 / 4OSDTitle, time, video loss, camera lock, motion detectionRecordingVideo/Audio CompressionH.264 / G.711Record ResolutionRecord Resolution1080p (1920 x 1080) / 720p (1280 x 720)Record Resolution1080p (1920 x 1080) / 720p (1280 x 720)Record Resolution1080p (1920 x 1080) / 720p (1/25fps) / Sub: D1 (1~12fps)Record ModesManual / Schedule (Regular [Continuous], MD) / StopBackup AddesUSB Device / NetworkBackup ModesUSB Device / NetworkEthernetR-45 port (10/100M)Max. User Access128 usersRemote ViewiOS (iPhone, iPad); Android devices, Windows PhoneStorageInternal HDD1 SATA port / 1TB surveillance hard drive (installed)MaxiliaryK5232N/ARestas1 port, for PTZ ControlPower SupplyDC12V/2AOperating Environment-10 ~+55°C / 10~90%RH / 86~106kpaDimensions325mm x 245mm x 45mm (Mini 1U)		Video Input	4 channel BNC
Note of upperTHOM / TOGAPisplayVideo Output1 HDMI / 1 VGAPreview Resolution1920 x 1080, 1280 x 1024, 1280 x 720, 1024 x 768, 800 x 600Display Split1 / 4OSDTitle, time, video loss, camera lock, motion detectionRecord Resolution1080p (1920 x 1080) / 720p (1280 x 720)Record Resolution1080p (1920 x 1080) / 720p (1280 x 720)Record RateMain: 1080p (1~12fps), 720p (1~25fps) / Sub: D1 (1~12fps)Record ModesManual / Schedule (Regular [Continuous], MD) / StopBackup ModesUSB Device / NetworkEthernetRJ-45 port (10/100M)Max. User Access128 usersRemote ViewiOS (iPhone, iPad); Android devices, Windows PhoneStorageInternal HDD1 SATA port / 1TB surveillance hard drive (installed)USB Interface2 ports (1 Rear), USB2.0RexastRS232N/AResolage SupplyDC12V/2AOperating Environment-10 ~+55°C / 10~90%RH / 86~106kpaDimensions325mm x 245mm x 45mm (Mini 1U)		Audio Input	4 channel RCA
Preview Resolution1920 x 1080, 1280 x 1024, 1280 x 720, 1024 x 768, 800 x 600Display Split1 / 4OSDTitle, time, video loss, camera lock, motion detectionVideo/Audio CompressionH.264 / G.711Record Resolution1080p (1920 x 1080) / 720p (1280 x 720)Record RateMain: 1080p (1~12fps), 720p (1~25fps) / Sub: D1 (1~12fps)Record ModesManual / Schedule (Regular [Continuous], MD) / StopBackup AgeEthernetRetord WodesUSB Device / NetworkEthernetRJ-45 port (10/100M)Max. User Access128 usersRemote ViewiOS (iPhone, iPad); Android devices, Windows PhoneStorageInternal HDD1 SATA port / 1TB surveillance hard drive (installed)NatiliaryRS232N/AResds1 port, for PTZ ControlPower SupplyDC12V/2AOperating Environment-10 ~+55°C / 10~90%RH / 86~106kpaDimensions325mm x 245mm x 45mm (Mini 1U)		Audio Output	1 channel RCA
DisplayDisplay Split1 / 4Display Split1 / 4OSDTitle, time, video loss, camera lock, motion detectionYideo/Audio CompressionH.264 / G.711Record Resolution1080p (1920 x 1080) / 720p (1280 x 720)Record RateMain: 1080p (1~12fps), 720p (1~25fps) / Sub: D1 (1~12fps)Record ModesManual / Schedule (Regular [Continuous], MD) / StopBackup & NetworkEthernetRenote ViewUSB Device / NetworkEthernetRJ-45 port (10/100M)Max. User Access128 usersRemote ViewiOS (iPhone, iPad); Android devices, Windows PhoneStorageInternal HDD1 SATA port / 1TB surveillance hard drive (installed)MaxiliaryRS232N/ARS4851 port, for PTZ ControlPower SupplyDC12V/2AOperating Environment-10 ~+55°C / 10~90%RH / 86~106kpaDimensions325mm x 245mm x 45mm (Mini 1U)	Display	Video Output	1 HDMI / 1 VGA
Display Split1/4Display SplitTitle, time, video loss, camera lock, motion detectionOSDTitle, time, video loss, camera lock, motion detectionPrecord RateH.264 / G.711Record RateNain: 1080p (1920 x 1080) / 720p (1280 x 720)Record ModesManual / Schedule (Regular [Continuous], MD) / StopBackup ModesUSB Device / NetworkBackup ModesUSB Device / NetworkEthernetRJ-45 port (10/100M)Max. User Access128 usersRemote ViewiOS (iPhone, iPad); Android devices, Windows PhoneStorageInternal HDD1 SATA port / 1TB surveillance hard drive (installed)USB Interface2 ports (1 Rear), USB2.0RxatliaryRS232N/ARower SupplyDC12V/2AOperating Environment-10 ~+55°C / 10~90%RH / 86~106kpaDimensions325mm x 245mm x 45mm (Mini 1U)		Preview Resolution	1920 x 1080, 1280 x 1024, 1280 x 720, 1024 x 768, 800 x 600
RecordingVideo/Audio CompressionH.264 / G.711Record Resolution1080p (1920 x 1080) / 720p (1280 x 720)Record RateMain: 1080p (1-212fps), 720p (1~25fps) / Sub: D1 (1~12fps)Record ModesManual / Schedule (Regular [Continuous], MD) / StopBackup AdesUSB Device / NetworkBackup ModesUSB Device / NetworkBackup Modes128 usersRemote ViewiOS (iPhone, iPad); Android devices, Windows PhoneStorageInternal HDD1 SATA port / 1TB surveillance hard drive (installed)USB Interface2 ports (1 Rear), USB2.0Rex851 port, for PTZ ControlPower SupplyDC12V/2AOperating Environment-10 ~+55°C / 10~90%RH / 86~106kpaDimensions325mm x 245mm x 45mm (Mini 1U)		Display Split	1/4
Record Resolution1080p (1920 x 1080) / 720p (1280 x 720)Record RateMain: 1080p (1~12fps), 720p (1~25fps) / Sub: D1 (1~12fps)Record ModesManual / Schedule (Regular [Continuous], MD) / StopBackup ModesUSB Device / NetworkBackup Access128 usersRemote ViewiOS (iPhone, iPad); Android devices, Windows PhoneStorageInternal HDD1 SATA port / 1TB surveillance hard drive (installed)USB Interface2 ports (1 Rear), USB2.0Rex32N/ARes32N/AGeneralPower SupplyDC12V/2AOperating Environment-10 ~+55°C / 10~90%RH / 86~106kpaDimensions325mm x 245mm x 45mm (Mini 1U)		OSD	Title, time, video loss, camera lock, motion detection
RecordingRecord RateMain: 1080p (1~12fps), 720p (1~25fps) / Sub: D1 (1~12fps)Record ModesManual / Schedule (Regular [Continuous], MD) / StopBackup ModesUSB Device / NetworkBackup ModesUSB Device / NetworkEthernetRJ-45 port (10/100M)Max. User Access128 usersRemote ViewiOS (iPhone, iPad); Android devices, Windows PhoneStorageInternal HDD1 SATA port / 1TB surveillance hard drive (installed)USB Interface2 ports (1 Rear), USB2.0AuxiliaryRS232N/ARS4851 port, for PTZ ControlPower SupplyDC12V/2AOperating Environment-10~+55°C / 10~90%RH / 86~106kpaDimensions325mm x 245mm x 45mm (Mini 1U)		Video/Audio Compression	H.264 / G.711
Record RateMain: 1080p (1~12fps), 720p (1~25fps) / Sub: D1 (1~12fps)Record ModesManual / Schedule (Regular [Continuous], MD) / StopBackup ABackup ModesUSB Device / NetworkBackup AEthernetRJ-45 port (10/100M)Max. User Access128 usersRemote ViewiOS (iPhone, iPad); Android devices, Windows PhoneStorageInternal HDD1 SATA port / 1TB surveillance hard drive (installed)USB Interface2 ports (1 Rear), USB2.0AuxiliaryRS232N/ARS4851 port, for PTZ ControlPower SupplyDC12V/2AOperating Environment-10 ~+55°C / 10~90%RH / 86~106kpaDimensions325mm x 245mm x 45mm (Mini 1U)	Decording	Record Resolution	1080p (1920 x 1080) / 720p (1280 x 720)
Backup KoreBackup ModesUSB Device / NetworkBackup ModesUSB Device / NetworkEthernetRJ-45 port (10/100M)Max. User Access128 usersRemote ViewIOS (iPhone, iPad); Android devices, Windows PhoneStorageInternal HDD1 SATA port / 1TB surveillance hard drive (installed)MaxiliaryUSB Interface2 ports (1 Rear), USB2.0RS232N/ARS4851 port, for PTZ ControlPower SupplyDC12V/2AOperating Environment-10 ~+55°C / 10~90%RH / 86~106kpaDimensions325mm x 245mm x 45mm (Mini 1U)	Recording	Record Rate	Main: 1080p (1~12fps), 720p (1~25fps) / Sub: D1 (1~12fps)
Backup & Network Ethernet RJ-45 port (10/100M) Max. User Access 128 users Remote View iOS (iPhone, iPad); Android devices, Windows Phone Storage Internal HDD 1 SATA port / 1TB surveillance hard drive (installed) Auxiliary USB Interface 2 ports (1 Rear), USB2.0 RS485 1 port, for PTZ Control Power Supply DC12V/2A Operating Environment -10 ~+55°C / 10~90%RH / 86~106kpa Dimensions 325mm x 245mm x 45mm (Mini 1U)		Record Modes	Manual / Schedule (Regular [Continuous], MD) / Stop
Network Max. User Access 128 users Remote View iOS (iPhone, iPad); Android devices, Windows Phone Storage Internal HDD 1 SATA port / 1TB surveillance hard drive (installed) Auxiliary USB Interface 2 ports (1 Rear), USB2.0 RS485 1 port, for PTZ Control Power Supply DC12V/2A Operating Environment -10 ~+55°C / 10~90%RH / 86~106kpa Dimensions 325mm x 245mm x 45mm (Mini 1U)		Backup Modes	USB Device / Network
Max. Oser Access T28 Users Remote View iOS (iPhone, iPad); Android devices, Windows Phone Storage Internal HDD 1 SATA port / 1TB surveillance hard drive (installed) Auxiliary USB Interface 2 ports (1 Rear), USB2.0 RS232 N/A RS485 1 port, for PTZ Control Power Supply DC12V/2A Operating Environment -10 ~+55°C / 10~90%RH / 86~106kpa Dimensions 325mm x 245mm x 45mm (Mini 1U)	Backup &	Ethernet	RJ-45 port (10/100M)
Storage Internal HDD 1 SATA port / 1TB surveillance hard drive (installed) Muxiliary USB Interface 2 ports (1 Rear), USB2.0 Auxiliary RS232 N/A RS485 1 port, for PTZ Control Power Supply DC12V/2A Operating Environment -10 ~+55°C / 10~90%RH / 86~106kpa Dimensions 325mm x 245mm x 45mm (Mini 1U)	Network	Max. User Access	128 users
Auxiliary USB Interface 2 ports (1 Rear), USB2.0 RS232 N/A RS485 1 port, for PTZ Control Power Supply DC12V/2A Operating Environment -10 ~+55°C / 10~90%RH / 86~106kpa Dimensions 325mm x 245mm x 45mm (Mini 1U)		Remote View	iOS (iPhone, iPad); Android devices, Windows Phone
Auxiliary RS232 N/A RS485 1 port, for PTZ Control Power Supply DC12V/2A Operating Environment -10 ~+55°C / 10~90%RH / 86~106kpa Dimensions 325mm x 245mm x 45mm (Mini 1U)	Storage	Internal HDD	1 SATA port / 1TB surveillance hard drive (installed)
RS485 1 port, for PTZ Control Power Supply DC12V/2A Operating Environment -10 ~+55°C / 10~90%RH / 86~106kpa Dimensions 325mm x 245mm x 45mm (Mini 1U)		USB Interface	2 ports (1 Rear), USB2.0
Power Supply DC12V/2A General Operating Environment -10 ~+55°C / 10~90%RH / 86~106kpa Dimensions 325mm x 245mm x 45mm (Mini 1U)	Auxiliary	RS232	N/A
General Operating Environment -10 ~+55°C / 10~90%RH / 86~106kpa Dimensions 325mm x 245mm x 45mm (Mini 1U)		RS485	1 port, for PTZ Control
General Dimensions 325mm x 245mm x 45mm (Mini 1U)	General	Power Supply	DC12V/2A
Dimensions 325mm x 245mm x 45mm (Mini 1U)		Operating Environment	-10 ~+55℃ / 10~90%RH / 86~106kpa
Weight 1.5kg (without HDD)		Dimensions	325mm x 245mm x 45mm (Mini 1U)
		Weight	1.5kg (without HDD)

Specifications - Digital Video Recorder

Main Processo

Specifications - Cameras			
Camera	Cameras Included	4 x VSCVI1MPFBIR	
	Image Sensor	1/3"1.3 Megapixel CMOS	
	Lens	3.6mm Fixed Lens	
	Angle of View	70°	
	Minimum Illumination	0.05 Lux at F1.2 (Colour) / 0 Lux IR Active	
	Day/Night	Auto (ICR) / Colour / B&W	
	Transmission Distance	Over 500m via 75-3 coaxial cable	
Video	Video Compression	H.264 / MJPEG	
	Resolution	720p (1280x720) / D1 (704x576)	
	Frame Rate	720p (25fps)	
	Video Output	BNC CVI HD output / CVBS SD output (switchable)	
General	Ingress Protection	IP66	
	Vandal Resistant	No	
	Maximum Infrared Range	20m	
	Power Input	DC12V±10%	
	Operating Environment	-30° to 60°C / RH95% (max)	