




Alarm notifications via SMS.

Watchguard™ Contact ID to SMS Communicator

The WGSMSB is a wireless GSM communicator which is used as an SMS backup for alarm panels. The communicator sends SMS alerts over GPRS to notify the up to 5 users and/or monitoring stations when the alarm is triggered.

- Notify up to 5 users via SMS for alarm events, supervision, GPRS fail, power loss and more * SIM card not included
- Compatible for use with most modern alarm panels
- Easy to install plug-and-play design & sturdy metal case
- Configurable from PC via USB and SMS commands
- Backup rechargeable battery, SMS alert when power lost
- Supports 3 communication modes: GPRS, SMS and PSTN
- Supports 2 different CMS centers (IP addresses / DNS server)

Model		WGSMSB
Product	Product Image	
	GSM 3G Frequency	850 / 900 / 1800 / 1900 MHz, 3G optional
Network	PSTN Protocol	Ademco Contact ID SIA DC-05
	GPRS Protocol	SIA DC-09-2007 / SIA DC-09-2012
	GSM Communication Ways	TCP/IP via GPRS
	Message Transmission Protocols	SIA DC-09-2007 / SIA DC-09-2012
	SIM Card	3V SIM card support
	Max. Stored Phone Numbers	5 phone numbers for alarm SMS
	Antenna	50 Ω SMA Antenna interface
Power	Message Transmission Protocols	SIA DC-09-2007 / SIA DC-09-2012
	Outputs	OUT1 / OUT2 / OC type, commutates voltage of up to 30 V and direct current of up to 1 A
	Power Supply	9~12VDC
	Power Consumption	20~30mA (Standby) <270mA (Active)
	Backup Battery	3.7V/900mAH Li-ion, rechargeable
	Configuration	USB port / SMS commands
	Operating Temperature	-20 ~ +60°C / 90%RH (max.)
Dimensions	130 x 74 x 27mm	
Weight	0.50kg	