

## 1080p Full HD 20m Infrared HDCVI Bullet Camera

## Model: VSCVI2MPFBIRV2-6


|   | Specifications |                        |  |
|---|----------------|------------------------|--|
|   |                | Camera Style           | Weatherproof Mini Bullet                           |
|   | General        | Image Sensor           | 1/3" 2.4 Megapixel CMOS                            |
|   |                | Effective Pixels       | 1984 (H) x 1225 (V)                                |
|   |                | Signal Noise Ratio     | > 50dB   |
| SECURVIEN<br>DEGE DE<br>Color camera          |                | Lens                   | 6mm Fixed Lens                                     |
|   | 2              | Angle of View          | 53.4°  |
|   | =              | Electronic Shutter     | 1/3 ~ 1/100,000s                                   |
|   | Ξ              | Minimum Illumination   | 0.05 Lux at F1.2 (Colour) / 0 Lux IR Active        |
|   | =              | Day/Night              | Auto (ICR) / Colour / B&W                          |
|   |                | White Balance          | Auto   |
|   |                | Noise Reduction        | 2D / 3D  |
|   | Camera         | Gain Control           | Auto   |
|   |                | Backlight Compensation | BLC / HLC / DWDR                                   |
|   |                | Audio Input            | N/A  |
|   |                | Audio Compression      | N/A  |
|   |                | Transmission Distance  | Over 300m via 75-3 coaxial cable                   |
|   |                | Synchronisation        | Internal   |
|   |                | OSD Menu               | Support  |
|   |                | Alarm Interface        | N/A  |
|   |                | Video Compression      | H.264 / MJPEG                                      |
|   | 1.6.1          | Resolution             | 1080p (1920×1080) / 720p (1280×720) / D1 (704x576) |
|   | Video          | Frame Rate             | 1080p / 720p (25fps)                               |
|   |                | Video Output           | BNC CVI HD output / CVBS SD output (switchable)    |
| FIXED MAX. DISTANCE IP66 RATED DAY/NIGHT      |                | Ingress Protection     | IP66   |
|   |                | Vandal Resistant       | No   |
|   |                | Maximum Infrared Range | 20m  |
|   |                | Power Input            | DC12V±10%  |
|   | Environment    | Power Consumption      | < 4.5W   |
| rview Victory Series VSCVI2MPFBIRV2 is a 2.4  |                | Dimensions             | 70 x 66 x 160mm                                    |
| el, fixed lens, infrared bullet camera and is |                | Weight                 | 0.38kg   |
|   |                | -                      |  |

The Securview Victory Series VSCVI2MPFBIRV2 is a 2.4 megapixel, fixed lens, infrared bullet camera and is capable of providing 1080p Full High Definition footage over coaxial cable.

It uses the HDCVI video transmission standard which enables transmission distance up to 300m (1080p using 75-3 coax) with low latency and low interference.

Its compact size and IP66 rating makes it a perfect surveillance solution across a wide range of applications.

This camera is only compatible with digital video recorders in the Securview Victory Series.



Operating Environment -30° to 60°C / RH95% (max)



Your Securview Victory Series dealer: