



High capacity, HD+ quality.

Professional 32 Channel Network Video Recorder

Model: NVR32PR0216P

- Records up to 5.0 megapixel (2560 x 1920)
- Up to 200Mbps incoming bandwidth
- 8x SATA ports for up to 32TB HDD capacity
- Remote view in seconds with setup via QR code
- HDMI & VGA simultaneous video output
- Built-in 16 port Power over Ethernet (PoE)
- Backup via USB device, network or DVD-RW
- Remote view for iOS, Android & Windows Phone



www.vip-vision.com

Professional 32 Channel Network Video Recorder

Model: NVR32PR0216P





	System	, ,	
		Video Input	32 channel
		Two-way Talk	1 channel input / 1 channel output / RCA
	Display	Video Output	HDMI / VGA / TV (BNC)
		Resolution	1920 x 1080 / 1280 x 1024 / 1280 x 720 /
		Display Split	1/4/8/9/16
		OSD	Camera title, Time, Video loss, Camera loc
	Recording	Video Compression	H.264 / MJPEG
		Resolution	5MP(2560x1920) / 3MP(2048x1536) / 108 720P(1280x720)
		Record Rate	Max. 200Mbps (eg. 32 channels 2.0MP at
		Bit Rate	48~ 8192kbps
		Dosard Madas	Manual / Schodula (Dogular [Continuous]

Product Overview

The VIP Vision NVR32PRO216P is a 32 channel network video recorder, designed as an immediate and customisable high definition IP surveillance solution. Installation of HD IP CCTV is simple with the NVR32PRO216P. It features a built-in 16 port Power over Ethernet (PoE) switch, supplying camera power, video, audio and PTZ control data across a single ethernet cable.


The NVR supports up to 200Mbps incoming bandwidth and can record at resolutions beyond full HD video up to 5.0MP (2560 x 1920). Adjusting recording settings, exporting footage and live viewing camera streams are performed through an easy to use user interface.

This NVR supports up to 32TB of internal storage and features continuous recording. When the internal storage is full, the NVR will automatically record over the oldest footage. Accessing footage and changing settings remotely is possible from a local PC or over the internet via the NVR web interface.

Smartphone and tablet remote viewing is available for iOS (iPhone, iPad), Google Android and Microsoft Windows Phone via free applications and can be configured in seconds using the remote view QR code

The NVR32PRO216P can backup footage to external USB devices, eSATA devices, an internal DVD-RW burner (optional) as well as via the local network.

Specifications					
	Main Processor	Dual-core embedded processor			
System	Operating System	Embedded Linux			
	Video Input	32 channel			
	Two-way Talk	1 channel input / 1 channel output / RCA			
	Video Output	HDMI / VGA / TV (BNC)			
Display	Resolution	1920 x 1080 / 1280 x 1024 / 1280 x 720 / 1024 x 768			
Display	Display Split	1/4/8/9/16			
	OSD	Camera title, Time, Video loss, Camera lock, Motion detection			
	Video Compression	H.264 / MJPEG			
	Resolution	5MP(2560x1920) / 3MP(2048x1536) / 1080P(1920x1080) / 720P(1280x720)			
Recording	Record Rate	Max. 200Mbps (eg. 32 channels 2.0MP at 5Mbps)			
	Bit Rate	48~ 8192kbps			
	Record Modes	Manual / Schedule (Regular [Continuous], MD, Alarm) / Stop			
	Record Interval	1~120 min (default: 60 min) / Pre: 1~30s / Post: 10~300s			
	Alarm Input / Output	16 channels / 4 channels			
Detection	Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Buzzer & Screen tips			
	Video Detection	Motion Detection, MD Zones: 396(22× 18), Video Loss & Camera Blank			
	Sync Playback	1/4/9/16			
Playback & Backup	Search Modes	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search			
	Backup Modes	USB Device / Network / eSATA Device / Internal SATA burner			
	Ethernet	1 RJ-45 port (10/100/1000Mbps)			
	Power over Ethernet	16 ports (IEEE802.3at)			
Network	Network Functions	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, IP Search			
	Max. User Access	128 users			
	Remote View	iOS (iPhone, iPad) / Android devices / Windows Phone			
Storage	Internal HDD	8 SATA ports, up to 32TB, RAID / 1 eSATA port			
	USB Interface	3 ports: 1 x Rear USB3.0 / 2 x Front USB2.0			
Auxiliary	RS232	1 port for PC communication & keyboard			
	RS485	1 port for PTZ control			
	Power Supply	100 ~ 240VAC, 50 ~ 60Hz			
	Power Consumption	NVR: 40W (without HDD)			
General	Operating Environment	-10 ~ 55°C / 10 ~ 90%RH / 86 ~ 106kpa			
	Dimensions	440 x 460 x 89mm / 2U			
	Weight	6.5kg (without HDD)			



Your VIP Vision IP surveillance dealer: