



# Peak quality & versatility.

## Professional Series: Motorised lens HDCVI dome available in 8.0MP

With high resolution image quality up to 4K and a compact, weather resistant aluminium body, the G-Body series from Securview captures excellent video footage, long range infrared, and zero image distortion with its flat lens cover.

- Stream up to UHD/4K/8.0MP (3840 x 2160) at 15fps
- Motorised varifocal 3.7~11mm lens with fixed iris
- Large 1/2" sensor for excellent low light performance
- Smart infrared illumination, up to 60m range
- HDCVI / AHD / TVI / CVBS switchable via DIP switch
- Up to 700m video transmission over coaxial cable
- True WDR (120dB) and 2D/3D noise reduction
- IP67 rated weather resistant metal housing



**Ultra HD Recording Over Coax**



**Compatible With Any Coax DVR**



**Superb Low Light Performance**

Model		VSCVI-8DIRMG	
Camera	Camera Style		G Body
	Image Sensor		1/2" 8.0 Megapixel CMOS
	Effective Pixels		3840 (H) x 2160 (V)
	Signal Noise Ratio		> 65dB
	Lens		3.7mm ~ 11mm F1.5 Motorised Lens, fixed iris
	Angle of View		112° (wide) ~ 46° (tele)
	Focus		Fixed / 1.8m Min. Focus Distance
	Minimum Illumination		0.005 Lux at F1.5 (Colour) / 0 Lux IR Active
	Electronic Shutter		1/4s ~ 1/100,000s
	Day/Night		Auto (ICR) / Colour / B&W
	Infrared Range		60m
	White Balance		Auto / Manual
	Noise Reduction		2D / 3D
Video	Gain Control		Auto
	Lighting Compensation		BLC / HLC / WDR (120dB)
	Resolution		8.0MP (3840 x 2160) to CIF (352 x 288)
DORI	Frame Rate		15fps (8.0MP) / 20fps (6.0MP) / 25fps (4.0MP and lower)
	Transmission Distance		Rated for up to 700m via 75-3 coaxial cable (performed in ideal test conditions)
	DORI Distance	Detect	83m (wide) / 190m (tele)
		Observe	33m (wide) / 76m (tele)
Recognise		17m (wide) / 38m (tele)	
Identify		8m (wide) / 19m (tele)	
Interface	Audio Input		Built-in Microphone / 1 Input
	Alarm Interface		N/A
	Video Output		1 x HDCVI / AHD / TVI / Composite video output (switchable via DIP switch)
	Synchronisation		Internal
	OSD Menu		Support
Environmental	Ingress Protection		IP67
	Vandal Resistant		N/A
	Housing		Aluminium
	Power Input		12VDC
	Power Consumption		< 9.5W
	Dimensions		Ø122mm x 107mm
	Weight		0.59kg
Operating Environment		-30° to 60°C / RH90% (max)	
Accessories	Diagram		
	Accessories		
	Models		