



## Highly adjustable LED Flood Lighting










LFL-F Series: Adjustable flood lighting in 480W, 720W & 960W models

The ENSA™ LFL-F series of LED flood lights features versatile lighting install options including 360° rotatable light modules and 140° tilt. Create flexible installs using the 250° double mounting bracket with attached metal compasses for precise mounting.

Delivers incredible illumination up to 165lm/W, all in a robust and weather resistant aluminium housing making it perfect for both indoor and outdoor commercial and industrial environments.

- Incredible luminous efficacy LED flood lighting (165lm/W)
- Available in 6500K cool white colour temperature
- IP66 weather resistant, suitable for outdoor applications
- Rotatable light modules up to 360° with 140° tilt
- Adjustable 250° double bracket with metal compass
- Long lifespan LED lighting: rated up to 50,000 hours

## Series Specifications

Model	LFL-F480-C	LFL-F720-C	LFL-F960-C																																																						
Product Image																																																									
Series Name	LFL-F Series LED Flood Light																																																								
<b>Optical</b>																																																									
Luminous Flux	79,200lm	118,800lm	158,400lm																																																						
Luminous Efficacy	165lm/W																																																								
Colour Temperature	6500K																																																								
Colour Rendering Index	> 70																																																								
Beam Angle	60°																																																								
Light Decay	<15% at 20,000 hours																																																								
Rated Lifespan	50,000 hours																																																								
<b>Electrical</b>																																																									
Power Consumption	480W	720W	960W																																																						
Input Voltage	90 ~ 305VAC, 50/60Hz																																																								
Power Factor	> 0.95																																																								
Dimmable	N/A																																																								
<b>General</b>																																																									
Ingress Protection	IP66																																																								
Plug / Socket / Base	3-pin AC plug																																																								
Reflector / Diffuser	Aluminium / Polycarbonate																																																								
Housing Adjustments	Rotatable light modules up to 360° with 140° tilt, 250° adjustable double mounting bracket																																																								
Operating Environment	-40° ~ 60°C																																																								
Dimensions	536 x 165 x 579mm	691 x 202 x 579mm	846 x 202 x 579mm																																																						
Weight	12.0kg	15.8kg	19.9kg																																																						
<b>Photometry</b>																																																									
Illuminance at a Distance	 <table border="1"> <thead> <tr> <th>Distance (m)</th> <th>Centre Beam Avg (lx)</th> <th>Beam Diameter (m)</th> </tr> </thead> <tbody> <tr><td>5m</td><td>3548</td><td>4.87</td></tr> <tr><td>10m</td><td>887</td><td>9.75</td></tr> <tr><td>15m</td><td>394</td><td>14.63</td></tr> <tr><td>20m</td><td>222</td><td>19.50</td></tr> <tr><td>25m</td><td>142</td><td>24.38</td></tr> </tbody> </table>	Distance (m)	Centre Beam Avg (lx)	Beam Diameter (m)	5m	3548	4.87	10m	887	9.75	15m	394	14.63	20m	222	19.50	25m	142	24.38	 <table border="1"> <thead> <tr> <th>Distance (m)</th> <th>Centre Beam Avg (lx)</th> <th>Beam Diameter (m)</th> </tr> </thead> <tbody> <tr><td>5m</td><td>5263</td><td>4.87</td></tr> <tr><td>10m</td><td>1315</td><td>9.75</td></tr> <tr><td>15m</td><td>584</td><td>14.63</td></tr> <tr><td>20m</td><td>329</td><td>19.50</td></tr> <tr><td>25m</td><td>210</td><td>24.38</td></tr> </tbody> </table>	Distance (m)	Centre Beam Avg (lx)	Beam Diameter (m)	5m	5263	4.87	10m	1315	9.75	15m	584	14.63	20m	329	19.50	25m	210	24.38	 <table border="1"> <thead> <tr> <th>Distance (m)</th> <th>Centre Beam Avg (lx)</th> <th>Beam Diameter (m)</th> </tr> </thead> <tbody> <tr><td>5m</td><td>7056</td><td>4.87</td></tr> <tr><td>10m</td><td>1764</td><td>9.75</td></tr> <tr><td>15m</td><td>784</td><td>14.63</td></tr> <tr><td>20m</td><td>441</td><td>19.50</td></tr> <tr><td>25m</td><td>282</td><td>24.38</td></tr> </tbody> </table>	Distance (m)	Centre Beam Avg (lx)	Beam Diameter (m)	5m	7056	4.87	10m	1764	9.75	15m	784	14.63	20m	441	19.50	25m	282	24.38
	Distance (m)	Centre Beam Avg (lx)	Beam Diameter (m)																																																						
	5m	3548	4.87																																																						
10m	887	9.75																																																							
15m	394	14.63																																																							
20m	222	19.50																																																							
25m	142	24.38																																																							
Distance (m)	Centre Beam Avg (lx)	Beam Diameter (m)																																																							
5m	5263	4.87																																																							
10m	1315	9.75																																																							
15m	584	14.63																																																							
20m	329	19.50																																																							
25m	210	24.38																																																							
Distance (m)	Centre Beam Avg (lx)	Beam Diameter (m)																																																							
5m	7056	4.87																																																							
10m	1764	9.75																																																							
15m	784	14.63																																																							
20m	441	19.50																																																							
25m	282	24.38																																																							
Luminous Light Distribution	 <p>Units: cd</p>	 <p>Units: cd</p>	 <p>Units: cd</p>																																																						

## Ordering Information

Type	Series	Wattage	Colour Temperature
LFL	-	480 (480W) 720 (720W) 960 (960W)	-
			C (Cool white)
LFL-F480-C: 480W LED Flood Light in Cool White			