



All-in-one CCTV solutions.

Professional Series: 4.0MP Surveillance Kits available with 4, 8 & 16 cameras

VIP Vision™ Professional Series CCTV kits offer broadcast-quality image performance with built-in Power over Ethernet for fast installations. Mix & match any equivalent priced dome or bullet camera to suit your installation needs.

- Records 4.0MP (2688 x 1520) up to real-time 25fps
- 4.0MP True WDR 50m IR dome cameras in 3.6mm
- IVS with tripwire, intrusion, motion detection & more
- Remote view in seconds with setup via QR code
- HDMI & VGA simultaneous video output
- Built-in Power over Ethernet (ePoE for 8/16 channel)
- Pre-installed 1TB/2TB/4TB surveillance grade HDD
- Remote view for iOS, Android & Windows Phone
 *Camera cabling sold separately



Beyond Full HD Recording & Live View



Extended PoE (ePoE) up to 800m



Comprehensive Remote View



4 Channel

8 Channel

16 Channel

4 Channel Professional NVR

- 4 port Power over Ethernet NVR
- Records 4.0MP at 25fps
- Pre-installed 1TB hard disk drive (additional backup via USB device or network)

8 Channel Professional NVR

- 8 port Extended Power over Ethernet NVR
- Records 4.0MP at 25fps
- Pre-installed 2TB hard disk drive (additional backup via USB device or network)

8 x 4.0MP Infrared Cameras

Stream up to 4.0MP (2688 x 1520)

IP67 rated metal housing for outdoor use

4 x 4.0MP Infrared Cameras

3.6mm (87°H / 48°V) fixed lens

• 8 x mini dome cameras

• 4 x mini dome cameras

- 3.6mm (87°H / 48°V) fixed lens
- Stream up to 4.0MP (2688 x 1520)
- IP67 rated metal housing for outdoor use

Accessories

- CAT5 patch cable for networking: 1 x 1.5m
- HDMI output cable: 1 x 1m
- 1 x NVR Remote and 1 x Mouse
- · Camera cabling sold separately

Accessories

- CAT5 patch cable for networking: 1 x 1.5m
- HDMI output cable: 1 x 1m
- 1 x NVR Remote and 1 x Mouse
- · Camera cabling sold separately

16 x 4.0MP Infrared Cameras

- 16 x mini dome cameras
- 3.6mm (87°H / 48°V) fixed lens
- Stream up to 4.0MP (2688 x 1520)
- · IP67 rated metal housing for outdoor use

Accessories

- CAT5 patch cable for networking: 1 x 1.5m
- HDMI output cable: 1 x 1m
- 1 x NVR Remote and 1 x Mouse
- · Camera cabling sold separately

16 Channel Professional NVR

- 16 port Extended Power over Ethernet NVR
- Records 4.0MP at 25fps
- Pre-installed 4TB hard disk drive (additional backup via USB device or network)

Technical Specifications

For full specifications and bracket compatibility, please see the individual unit web entry or datasheet.

NVR Model	NVR4PRO3	NVR8PRO7	NVR16PRO7
Product Image		HAROS EIII ()+	IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII
Video Input	4 channel	8 channel	16 channel
Two-way Talk	1 channel input / 1 channel	1 channel input / 1 channel output / RCA 1 channel input / 2 channel output / RCA	
Video Output	1 x HDMI / 1 x VGA	1 x HDMI / 1 x VGA	2 x HDMI / 2 x VGA
Maximum Resolution	Configurable from 8.0MP (3840 x 2160) to CIF	Configurable from 12.0MP (4000 x 3000) to CIF (352 x 288)	
Incoming Bandwidth	200Mbps	320Mbps	
Video Compression	H.265 / H.264	H.265 / H.264 / MJPEG / MPEG4	
Bit Rate	16 ~ 20Mbps per channel		
Alarm Input / Output	4 channels input / 2 channels relay output	4 channels input / 2 channels relay output	16 channels input / 6 channels relay output
Internal HDD	2 x SATA ports, up to 10TB each (1TB pre-installed)	2 x SATA ports, up to 10TB each (2TB pre-installed)	4 x SATA ports, up to 10TB each (4TB pre-installed)
Power Supply	48VDC, 2A	100 ~ 240VAC, 50 ~ 60Hz	

Camera Mode	el	VSIPE4MPVDMINIIRCB3.6		
Product Image	•			
Image Sensor		1/3" 4.0MP Progressive Scan CMOS		
Lens		3.6mm F2.0 Fixed Lens		
Min. Illuminat	ion	0.06 Lux/F2.0 (Color), 0 Lux/F2.0 (IR on)		
Infrared Range		50m		
Lighting Compensation		BLC / HLC / WDR (120dB)		
Resolution		4.0MP (2688 x 1520) to CIF (352 x 288)		
Frame Rate	Main	4.0MP (1 ~ 25fps)		
	Sub	D1 (1 ~ 25fps)		
	Third	720p (1 ~ 25fps)		
Audio Input		Built-in Microphone / Compression: G.711a, G.711Mu, AAC, G.726		
Smart Functio	ns	Tripwire, Intrusion, Object Abandoned/Missing, Face Detection, Motion Detection (4 zones), Region of Interest (4 zones), Privacy Masking (4 zones), Smart Infrared		
Weather/Vand	lal Resist	IP67		
Power Input 12VDC / PoE (802.3af)		12VDC / PoE (802.3af)		

Your local VIP Vision™ IP solutions professional: