



Double Full HD Resolution

Compact Series: 4.0MP motorised lens IP surveillance kits in 4, 8 & 16 channels

The Watchguard™ 4.0MP surveillance kits with up to 4x optical zoom cameras, are built for rapid installation in any home or small business, so that you can focus on what you want to see.

- Records up to 4.0MP (2560 x 1440 pixels) at 20fps
- Up to 60m infrared range; true day/night (auto ICR)
- Motion & face detection, region of interest and more
- Pre-fitted 1TB / 2TB / 4TB surveillance-grade HDDs
- IP67 rated, metal housing cameras; IK10 rated domes
- Native Ultra HD live view on 4K monitors via HDMI
- Built-in Power over Ethernet (PoE) for easy installation
- Power via 12VDC or Power over Ethernet (802.3af)
- Mix & match any equivalent price dome/bullet camera
- Remote view for iOS, Android & Windows Phone



Double Full HD Resolution






Built-in PoE for plug & play install



Comprehensive Remote View




Choose from three comprehensive, ready to install packages.




The Watchguard™ Compact Series offers complete 4, 8 and 16 channel network surveillance packages, purpose-built for rapid installation and impressive results.

Kit Model	NVRKIT-C441M	NVRKIT-C842M	NVRKIT-C1644M
Kit Image			
Network Video Recorder	NVR4COM2 with 4 Port PoE & 1 x SATA Bay	NVR8COM2 with 8 Port PoE & 1 x SATA Bay	NVR16COM2 with 16 Port PoE & 2 x SATA Bay
Internal Storage	1TB Surveillance HDD	2TB Surveillance HDD	4TB Surveillance HDD
Standard Cameras	2 x VSIPC-4DIRMD 4.0MP 30m IR Vandal Dome 2 x VSIPC-4BIRMG 4.0MP 60m IR Bullet	4 x VSIPC-4DIRMD 4.0MP 30m IR Vandal Dome 4 x VSIPC-4BIRMG 4.0MP 60m IR Bullet	8 x VSIPC-4DIRMD 4.0MP 30m IR Vandal Dome 8 x VSIPC-4BIRMG 4.0MP 60m IR Bullet
Included Accessories	1 x 1.5m CAT5 patch cable for networking / 1 x 1m HDMI output cable / 1 x NVR Remote and 1 x Mouse <i>*Camera cabling sold separately*</i>		

Included & optional surveillance kit components

For specifications and additional product options, please see the individual unit web entry or datasheet.

Kit Model	NVR4COM2	NVR8COM2	NVR16COM2
Product Image			
Video Input	4 channel	8 channel	16 channel
Video Output	1 x HDMI, 1 x VGA		
Recording Resolution	Configurable from 8.0MP (3840 x 2160) to CIF (352 x 288)		
Incoming Bandwidth	80Mbps		200Mbps
Video Compression	H.265 / H.264		
Bit Rate	16 ~ 20Mbps per channel		
Ethernet	1 x RJ-45 port (10/100Mbps)		1 x RJ-45 port (10/100/1000Mbps)
PoE	4 ports (IEEE802.3at/af)	8 ports (IEEE802.3at/af)	16 ports (IEEE802.3at/af)
Remote View	iOS (iPhone, iPad) / Android devices / Windows Phone* (limited functionality)		
Internal HDD	1 x SATA port up to 10TB max, 10TB HDD Capacity		2 x SATA port up to 10TB max, 20TB HDD Capacity

Camera Model	VSIPC-4BIRMG	VSIPC-4DIRMD	VSIPC-4DIRMG (Optional)
Product Image			
Lens	2.8mm~12mm F1.8 Motorised Varifocal Lens, Horizontal: 94°~33°, Vertical: 51°~19° (4x Optical Zoom)		
Image Sensor	1/3" 4.0MP Progressive Scan CMOS		
Lighting Compensation	BLC / HLC / Digital WDR		
Resolution	4.0MP (2560 x 1440) to CIF (352 x 288)		
Infrared Range	4 x Infrared LED, 60m range Auto/manual on/off control	2 x Infrared LED, 30m range Auto/manual on/off control	2 x Infrared LED, 50m range Auto/manual on/off control
Frame Rate	Main Stream: 4.0MP (1 ~ 20fps) / Sub Stream: D1 (1 ~ 20fps)		
Smart Functions	Motion Detection (4 zones), Region of Interest (4 zones), Privacy Masking (4 zones), Smart Infrared		
Housing	Metal enclosure, IP67 weather-rated, IK10 vandal-rated (VSIPC-4DIRMD only)		
Power Supply	12VDC / PoE (802.3af) (Class 0)		
Suggested Products	Junction Box (VSBKTA134), Corner Wall Mount Camera Bracket (VSBKTA151), Dual Clamp Pole Mount (VSBKTA152E)	Junction Box (VSBKTA137), Dual Clamp Pole Mount (VSBKTA152E), Rain Cover (VSBKTA200W), Right Angle Wall Mount (VSBKTB203W), Recessed Ceiling Mount (VSBKTB200)	Junction Box (VSBKTA137), Dual Clamp Pole Mount (VSBKTA152E), Right Angle Wall Mount (VSBKTB203W)

Your local Watchguard™ IP surveillance professional: