



## Professional High Power LED Flood Lighting

LFL-G Series: Modular flood lighting with U-shape bracket in 240W & 480W

The ENSA™ LFL-G Series of LED flood lights is a flexible choice large scale lighting solutions. These high power lights feature dual bracket & light tilt adjustment for a smooth installation process, and are ideal in sports lighting applications and in large outdoor production and carpark facilities.

LFL-G Series flood lights are incredibly reliable with a rated lifespan up to 100,000 hours, and have versatile dimming options with both DALI and DMX control standards.

- High performance 160lm/W LED lighting efficiency
- Incredible light output at up to 81,600 lumens
- Narrow 30° beam angle, ideal for high installations
- 90° LED module tilt and 180° adjustable U-bracket
- High performance, long lifespan 5050 SMD LED package
- Optional dimming controlled via DALI & DMX standards
- Independent power box with efficient heat dissipation
- IP67 weather rated and IK10 vandal resistance

## Series Specifications

Model	LFL-G240	LFL-G480				
Product Image						
Series Name	LFL-G Series	LFL-G Series LED Flood Lights				
Optical						
Luminous Flux	38,400lm	81,600lm				
Luminous Efficacy	160lm/W	172lm/W				
LED Package	5050 SMD LEE	5050 SMD LEDs (120pcs/module)				
Colour Temperature	5000K cool white					
Colour Rendering Index	>80					
Beam Angle	30°					
Rated LED Lifespan	100,000 hours					
Electrical						
Power Consumption	240W	480W				
Input Voltage	100~277/347/480VAC					
Power Factor	> 0.95					
Dimming Technology	DALI / DMX (optional)					
General		IDC7				
Ingress Protection Driver Package	IP67  Meanwell LED driver, 3-pin AC plug					
Reflector / Diffuser	Polycarbonate lens					
Housing Adjustments	90° light tilt, 180° U-bracket tilt					
Operating Environment	-20° ~ 55°C					
Dimensions	460 x 230 x 75mm	460 x 460 x 75mm				
Net Weight	12.5kg	18kg				
Photometry	· · · · ·					
Illuminance at a Distance	90° 180° 90° 270° Units cd  90° 57200	90° 90 - 270° Units cd 90° 75° 57200 1114400 1228800 228800 30° 15° 0° 15° 30°				
Luminous Light Distribution	Centre Beam Avg (lx)  1.5m  2m  2m  28886  0.97  4m  7222  1.94  4.5m  5706  2.18  6m  3210  2.91	Centre Beam Avg (lx)  Seam Diameter (m)  Seam Diame				

## Ordering Information

Туре		Series	Wattage		Colour Temperature
LFL	-	G	240 (240W) 480 (480W)	-	C (Cool white)
LFL-G240-C: 240W LED Flood Light in Cool White					

## Diagram

