



## **Remote view from anywhere.**

## SLR-B Series: Solar CCTV surveillance with WiFi & 4G remote view options

Deliver surveillance to any location with the SLR-B Series Solar CCTV Surveillance Systems. These remote-view-enabled, standalone surveillance solutions are perfect in areas without network/power infrastructure. This may include black spot monitoring, on farms, or in temporary CCTV applications such as construction sites or at events.

- Standalone powered and networked IP surveillance
- Efficient 120/180W monocrystalline silicon solar panel
- 4G or long range WiFi integration for remote view
- Lasts several days from full charge in cloudy conditions
- 500/1200Wh lithium iron phosphate battery (LiFePo4)
- Built-in 40W microwave motion sensor LED area light with 10m detection range at 8m height (65° angle)
- Ø50~60mm pole mount diameter (pole not included)



Solar Powered IP Surveillance



WiFi or 4G Remote View Options



**Microwave Motion Area Light** 



## Solar CCTV Series | Series Specifications

Solar Panel				
lmage				
Panel Type	120W monocrystalline silicon panel 180W monocrystalline silicon panel			N monocrystalline silicon panel
Conversion Rate	Up to 21% efficiency			
Battery	500Wh Lithium Iron Phosphate (LiFePO4) 1200Wh Lithium Iron Phosphate (LiFePo 4) with Low Voltage Cutoff			
Panel Adjustment	-60° ~ 60° tilt adjustable w		· · · · · · · · · · · · · · · · · · ·	
Ingress Protection	IP65			
Wind Resistance	Up to 65m/s			
Dimensions	1321 x 525 x 161mm		1496 x 685 x 161mm	
Pole Diameter				
Area Light	Ø50 ~ 60mm			
Light Module	50W LED (3030 Philips), 9400lm (180lm/W)			
Light Characteristics	145° x 100° (batwing) beam angle / 5700K cool white / 50,000hrs rated lifespan			
Motion Detection	Microwave motion sensor, Ø8 ~ 15m range (at 10m height)			
Adjustable Settings	Normal & Morning time periods / Brightness on motion / On-time delay / Brightness after delay			
Light Adjustment	$-30^{\circ} \sim +30^{\circ}$ tilt adjustable twin LED module			
Camera				
Camera Options Connectivity	4.0MP Mini Al PTZ Dome 2.8 ~ 12mm Motorised lens 31.6° ~ 96.9° (4x optical zoom) Pan:0° ~ 355° / Tilt: 5° ~ 90° 			
Inclusions and Optional Accessories	Solar CCTV Assembly (included) Mounting kit with backing box and triple-clamp pole mount (pole not incl.)	Wester WD Purp	<b>D (included)</b> grade microSD card	AG LTE Wireless Access Point LTE connectivity up to 150Mbps speeds 4G: FDD-B1/B2/B3/B4/B5/B7/B8/B28, TDD-B40 *SIM card & service charges not included
Diagrams				525

Your local VIP Vision<sup>™</sup> IP solutions professional: