

# **Immediate HD Surveillance**

## Compact 8 Channel IP Surveillance Kit

## **Model: NVR8ENTPACK**

- 1.3MP surveillance kit with pre-installed 1TB HDD
- Records 1.3 megapixel (1280 x 960) at 25fps
- Easy install with built-in 8 port PoE switch
- HDMI and VGA simultaneous video output
- 8 x 1.3 megapixel weatherproof bullets/domes
- Easy remote view configuration via QR code
- View on iOS, Android & Windows Phone devices
- All required HDMI, CAT5 and power cables included



You deserve to feel safe, secure & protected™

## **Compact 8 Channel IP Surveillance Kit**

Model: NVR8ENTPACK





### **Package Includes**

- Watchguard<sup>™</sup> 8 Channel Compact NVR with built in PoE
- Pre-installed 1TB surveillance hard disk drive
- 4 x 1.3MP 30m infrared weather resistant bullets
- 4 x 1.3MP 30m infrared weather/vandal resistant domes
- CAT5 cabling for cameras: 4 x 10m, 2 x 20m, 2 x 30m
- CAT5 patch cable for networking: 1 x 1.5m

#### **Product Overview**

The Watchguard NVR8ENTPACK is a compact, high definition surveillance system ideal for homes and small businesses.

This CCTV package includes 8 x 1.3 megapixel cameras capable of recording 1280 x 960 footage in real-time 25fps. They comprise 4 x weather resistant bullets; and 4 x vandal/weather resistant compact domes. The network video recorder has a built-in 4 port power over Ethernet switch, allowing easy plug and play installation. The NVR features H.264 compression and a pre-installed 1TB hard drive for weeks of continuous recording. Video quality and frame rate can also be adjusted to increase the recording time.

The NVR features continuous recording where old footage is overwritten when the hard drive is full. The NVR also includes motion detection recording, record scheduling and network feed access.

This NVR offers a comprehensive range of remote view options so you may monitor your premises on the go. You can connect to your Watchguard CCTV system via local and network PC; through applications available for iOS and Android operating devices; and for Windows Phone smartphones.

NVR Model	NVR8ENT		
System	NVROENI		
Main Processor	Dual-core embedded processor		
Operating System	Embedded Linux		
	8 channel		
Video Input	N/A		
Two-way Talk ONVIF Conformance	2.4 Conformance		
Display	HDMI / VGA		
Video Output Resolution			
	Configurable from 1920 x 1080 to 1024 x 768		
Display Split	1/4/8/9		
OSD	Title, time, video loss, camera lock, motion detection, record		
Recording	IL 2CA / MAIDEC		
Video Compression	H.264 / MJPEG		
Maximum Resolution	Configurable from 5.0MP(2560 x 1920) to CIF (352 x 288)		
Incoming Bandwidth	80Mbps		
Bit Rate	48~8192Kbps		
Detection			
Alarm Input / Output	N/A		
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Buzzer		
Video Detection	Motion (Zones: 396(22×18)), Video Loss, Camera Blank		
Playback & Backup			
Playback Sync	1/4/9		
Search Modes	Time/Date, Alarm, By Motion, Exact search, Smart search		
Backup Modes	USB Device / Network		
Network			
Ethernet	1 RJ-45 port (10/100M)		
Power over Ethernet	8 ports (IEEE802.3af)		
Max. User Access	128 users		
Remote View	iOS (iPhone, iPad) / Android devices / Windows Phone		
Storage			
Internal HDD	1TB pre-installed HDD		
Auxiliary			
USB Interface	2 ports: 1 x Front USB2.0 / 1 x Rear USB2.0		
Auxiliary Inputs	N/A		
General			
Power Supply	48VDC/2A		
Operating Environment	-10 ~ 55°C / 10 ~ 90%RH / 86 ~ 106kpa		
Dimensions	270 x 270 x 45mm		
Weight	0.70kg (without HDD)		
_			

Camera Model		VSIP1MPFBIRV3	VSIP1MPVDMINIIRC	
Camera				
Image Sensor		1/3" 1.3 Megapixel Progressive Scan CMOS		
Lens		3.6mm F1.8 Fixed Lens (70°)	3.6mm F1.6 Fixed Lens (70°)	
Day/Night		Auto (ICR) / Colour / B&W		
Backlight Com	pensation	BLC / HLC / DWDR		
Audio Input		N/A	Built-in Microphone	
Maximum Infra	ared Range	30m		
Smart Functions		N/A		
Video				
Resolution		Configurable from 1.3MP (1280 x 960) to CIF (352 x 288)		
Frame Rate	Main	1.3MP and lower (1 ~ 25fps)		
	Sub	D1 and lower (1 ~ 25fps)		
	Third	N/A		
Environment				
Ingress Protection		IP66 Weather Resistant		
Vandal Resistant		N/A	IK10 Vandal Resistant	
Power Input		12VDC / PoE (802.3af)		

Your local Watchguard™ professional: