



# HD surveillance made easy.

## **Professional 16 Channel IP Surveillance Kit**

Model: NVR16PR0PACK5

- Records 1.3MP (1280 x 960) at 25fps real-time
- 8 x 1.3 megapixel 30m IR IP66 bullet cameras
- 8 x 1.3 megapixel 30m IR IP66/IK10 dome cameras
- Remote view in seconds with setup via QR code
- Live view surveillance in Ultra HD resolution
- Built-in 16 port Power over Ethernet (PoE)
- Pre-installed 2TB surveillance hard disk drive
- Remote view for iOS, Android & Windows Phone



## **Professional 16 Channel IP Surveillance Kit**

Model: NVR16PR0PACK5



#### **Package Includes**

- VIP Vision<sup>™</sup> 16 Channel Professional NVR with built in PoE
- Pre-installed 2TB surveillance hard disk drive
- 8 x 1.3MP 30m infrared weather resistant bullet cameras
- 8 x 1.3MP 30m infrared weather/vandal resistant dome cameras
- CAT5 cabling for cameras: 8 x 10m, 4 x 20m, 4 x 30m
- CAT5 patch cable for networking: 1 x 1.5m

### **Product Overview**

The VIP Vision NVR16PROPACK5 is a complete 16 channel network surveillance system, built for rapid installation and impressive results. It is an ideal CCTV package for business and large residential applications, especially in retail and commercial environments.

It is easy to achieve excellent high definition security, up to 1.3 megapixel resolution at 25fps, with the NVR16PROPACK5. Connecting cameras is performed quickly thanks to the built-in 16 port power over Ethernet switch and included pre-terminated CAT5 cables.

This kit comes with a pre-installed 2TB surveillance-grade hard drive, providing reliable footage storage and faster installation. Footage can also be exported via USB device or over the network

Enabling remote view is just as simple as installation with the QR code configuration tool. Simply connect the NVR to the Internet and scan the QR code with your smartphone to automatically configure remote view on your device. Remote view compatible with iOS, Android and Windows Phone. QR code for iOS and Android only.

NVR Model	NVR16PRO5		
System			
Main Processor	Dual-core embedded processor		
Operating System	Dual-core embedded processor Embedded Linux		
Video Input	Embedded Linux 16 channel		
Two-way Talk			
ONVIF Conformance	1 channel input / 1 channel output / RCA 2.4 Conformance		
Display			
Video Output	2 x HDMI / VGA		
Resolution			
	Configurable from 3840 x 2160 to 1024 x 768		
Display Split OSD	1/4/8/9/16		
	Camera title, Time, Video loss, Camera lock, Motion detection		
Recording			
Video Compression	H.265 / H.264 / MJPEG		
Maximum Resolution	Configurable from 12.0MP(4000 x 3000) to CIF (352 x 288)		
Incoming Bandwidth	256Mbps		
Bit Rate	1 ~ 20Mbps		
Detection			
Alarm Input / Output	16 channels input / 6 channels relay output		
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Buzzer		
Video Detection	Motion (Zones: 396(22×18)), Video Loss, Camera Blank		
Playback & Backup			
Playback Sync	1/4/9/16		
Search Modes	Time/Date, Alarm, By Motion, Exact search, Smart search		
Backup Modes	USB Device / Network / eSATA Device / Internal SATA burner		
Network			
Ethernet	1 RJ-45 port (10/100/1000M)		
Power over Ethernet	16 ports (IEEE802.3af)		
Max. User Access	128 users		
Remote View	iOS (iPhone, iPad) / Android devices / Windows Phone		
Storage			
Internal HDD	4 SATA ports, up to 24TB		
Auxiliary			
USB Interface	3 ports: Rear USB3.0 / Front USB2.0		
Auxiliary Inputs	1 x RS232 / 1 x RS485 / 1 x eSATA		
General			
Power Supply	100 ~ 240VAC, 50 ~ 60Hz		
Operating Environment	-10 ~ 55°C / 10 ~ 90%RH / 86 ~ 106kpa		
Dimensions	440 x 405 x 76mm		
Weight	4.65kg (without HDD)		
Camera Model	VSIP1MPFBIRV3 VSIP1MPVDMINIIRC		
Camera			
Image Sensor	1/3" 1.3 Megapixel Progressive Scan CMOS		

Camera Model		VSIP1MPFBIRV3	VSIP1MPVDMINIIRC	
Camera				
Image Sensor		1/3" 1.3 Megapixel Progressive Scan CMOS		
Lens		3.6mm F1.8 Fixed Lens (70°)	3.6mm F1.6 Fixed Lens (70°)	
Day/Night		Auto (ICR) / Colour / B&W		
<b>Backlight Compensation</b>		BLC / HLC / DWDR		
Audio Input		N/A	Built-in Microphone	
Maximum Infrared Range		30m		
Smart Functions		N/A		
Video				
Resolution		Configurable from 1.3MP (1280 x 960) to CIF (352 x 288)		
Frame Rate	Main	1.3MP and lower (1 ~ 25fps)		
	Sub	D1 and lower (1 ~ 25fps)		
	Third	N/A		
Environment				
Ingress Protect	tion	IP66 Weather Resistant		
Vandal Resistant		N/A	IK10 Vandal Resistant	
Power Input		12VDC / PoE (802.3af)		

#### Your local VIP Vision<sup>™</sup> professional:

