



Amazing images & value.

Compact Series: 6.0MP fixed lens IP surveillance kits in 4, 8 & 16 channels

The Watchguard™ fixed lens surveillance kits are high performance CCTV systems for an affordable price. Packed with high resolution turret domes & built-in PoE for easy installation, they are the ideal solution for homes & businesses.

- Records up to 6.0MP (3072 x 2048 pixels) at 20fps
- 50m infrared distance & true wide dynamic range
- Tripwire, intrusion & face detection intelligent functions
- Pre-fitted 1TB / 2TB / 4TB surveillance-grade HDDs
- IP67 rated weather resistance, metal housing cameras
- Native Ultra HD live view on 4K monitors via HDMI
- Built-in Power over Ethernet (PoE) for easy installation
- Power via 12VDC or Power over Ethernet (802.3af)
- Backup video via external USB device or local network
- Remote view for iOS, Android & Windows smart device







Triple the resolution of Full HD

Built-in PoE for plug & play install

Remote view setup in seconds



Choose from three comprehensive, ready to install packages.

The Watchguard™ Compact Series offers complete 4, 8 and 16 channel network surveillance packages, purpose-built for rapid installation and impressive results.



Kit Specifications

For full specifications and bracket compatibility, please see the individual web entry or datasheet.

NVR Model	NVR4COM2	NVR8COM2	NVR16COM2
Product Image		11	
Video Input	4 channel	8 channel	16 channel
Video Output	1 x HDMI , 1 x VGA		
Recording Resolution	Configurable from 8.0MP (3840 x 2160) to CIF (352 x 288)		
Incoming Bandwidth	80Mbps		200Mbps
Video Compression	H.265 / H.264		
Bit Rate	16 ~ 20Mbps per channel		
Ethernet	1 x RJ-45 port (10/100Mbps)		1 x RJ-45 port (10/100/1000Mbps)
PoE	4 ports (IEEE802.3at/af)	8 ports (IEEE802.3at/af)	16 ports (IEEE802.3at/af)
Remote View	iOS (iPhone, iPad) / Android devices		
Internal HDD	1 x SATA port up to 10TB max, 10TB HDD Capacity		2 x SATA port up to 10TB max, 20TB HDD Capacity

Camera Model	VSIPC-6DIRC	
Product Image		
Image Sensor	1/2.9" 6.0MP Progressive Scan CMOS	
Lens	2.8mm F1.6 Fixed Lens, Horizontal: 98°, Vertical: 67°	
Lighting Compensation	HLC / BLC / True WDR (120dB)	
Video Resolution	6.0MP (3072 x 2048) to CIF (352 x 288)	
Infrared Range	1 x Infrared LED, 50m range, Auto/manual on/off control	
Frame Rate	Main Stream: 6.0MP (1 ~ 20fps)/4.0MP(1 ~ 25fps) / Sub Stream: D1 (1 ~ 20fps) / Third Stream: 1080p (1 ~ 20fps)	
Smart Functions	Tripwire, Intrusion, Abandoned/Missing Object Detection, Face Detection, Motion Detection, Region of Interest	
Housing	Metal enclosure, IP67 weather-rated	
Power Supply	12VDC / PoE (802.3af) (Class 0)	
Suggested Products	Junction Box (VSBKTA139), Wall Mount (VSBKTB204W), Pole Mount (VSBKTA152-E)	

Your local Watchguard™ IP surveillance professional: