

# Immediate HD Surveillance

## Compact 4 Channel IP Surveillance Kit (with Dome Cameras)

### Model: NVR4ENTPACK3D

- 1.3MP surveillance kit with pre-installed 1TB HDD
- Records 1.3 megapixel (1280 x 960) at 25fps
- Easy install with built-in 4 port PoE switch
- HDMI and VGA simultaneous video output
- 4 x 1.3 megapixel weather/vandal resistant dome cameras
- Easy remote view configuration via QR code
- View on iOS, Android & Windows Phone devices
- All required HDMI, CAT5 and power cables included

**Watchguard** 

You deserve to feel safe, secure & protected™

## **Compact 4 Channel IP Surveillance Kit**

Model: NVR4ENTPACK3D



#### **Package Includes**

- Watchguard<sup>™</sup> 4 Channel Compact NVR with built in PoE
- Pre-installed 1TB surveillance hard disk drive
- 4 x 1.3MP 30m infrared weather/vandal resistant dome cameras
- CAT5 cabling for cameras: 2 x 10m, 1 x 20m, 1 x 30m
- CAT5 patch cable for networking: 1 x 1.5m

#### **Product Overview**

The Watchguard NVR4ENTPACK3D is a compact, high definition surveillance system ideal for homes and small businesses.

This CCTV package includes 4 x 1.3 megapixel, weather/vandal resistant dome cameras, capable of recording 1280 x 960 footage in real-time 25fps. The network video recorder has a built-in 4 port power over Ethernet switch, allowing easy plug and play installation. The NVR features H.264 compression and a pre-installed 1TB hard drive for weeks of continuous recording. Video quality and frame rate can also be adjusted to increase the recording time.

The NVR features continuous recording where old footage is overwritten when the hard drive is full. The NVR also includes motion detection recording, record scheduling and network feed access.

This NVR offers a comprehensive range of remote view options so you may monitor your premises on the go. You can connect to your Watchguard CCTV system via local and network PC; through applications available for iOS and Android operating devices; and for Windows Phone smartphones.

		-
NVR Model		NVR4ENT3
System		
Main Processor		Dual-core embedded processor
Operating System		Embedded Linux
Video Input		4 channel
Two-way Talk		N/A
ONVIF Conformance		2.4 Conformance
Display		
Video Output		HDMI / VGA
Resolution		Configurable from 1920 x 1080 to 1024 x 768
Display Split		1/4
OSD		Title, time, video loss, camera lock, motion detection, record
Recording		
Video Compression		H.264 / MJPEG
Maximum Resolution		Configurable from 5.0MP(2560 x 1920) to CIF (352 x 288)
		80Mbps
Incoming Bandwidth Bit Rate		48~8192Kbps
	_	48~8192kbps
Detection		N/A
Alarm Input / Output		N/A
Trigger Events Video Detection		Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Buzzer
		Motion (Zones: 396(22×18)), Video Loss, Camera Blank
Playback & Ba	скир	
Playback Sync		
Search Modes		Time/Date, Alarm, By Motion, Exact search, Smart search
Backup Modes		USB Device / Network
Network		
Ethernet		1 RJ-45 port (10/100M)
Power over Ethernet		4 ports (IEEE802.3af)
Max. User Access		128 users
Remote View		iOS (iPhone, iPad) / Android devices / Windows Phone
Storage		
Internal HDD		1TB pre-installed HDD
Auxiliary		
USB Interface		2 ports: Rear USB2.0
Auxiliary Inputs		N/A
General		
Power Supply		48VDC/1.5A
Operating Environment		-10 ~ 55°C / 10 ~ 90%RH / 86 ~ 106kpa
Dimensions		205 x 205 x 45mm
Weight		0.50kg (without HDD)
Camera Model		VSIP1MPVDMINIIRC
Camera		
Image Sensor		1/3" 1.3 Megapixel Progressive Scan CMOS
Lens		3.6mm F1.6 Fixed Lens (70°)
Day/Night		Auto (ICR) / Colour / B&W
Backlight Compensation		BLC / HLC / DWDR
Audio Input		Built-in Microphone
Maximum Infrared Range		30m
Smart Functions		N/A
Video	13	IVA
		Configurable from 1 2MD (1200 - 0(0) to CIE (202 - 200)
Resolution	Main	Configurable from 1.3MP (1280 x 960) to CIF (352 x 288)
	Main	1.3MP and lower (1 ~ 25fps)
	Sub	D1 and lower (1 ~ 25fps)
Frame Rate	Third	N/A
	THING	
Environment		
		IP66 Weather Resistant
Environment	ion	IP66 Weather Resistant IK10 Vandal Resistant

Your local Watchguard<sup>™</sup> professional:

