



Modern access solutions.

Apartment Series: Touchscreen PoE IP intercom monitor

The Apartment Series touchscreen indoor monitor integrates with all IP video intercom solutions. The monitor is used for two-way talk with an apartment door station, featuring live-view of the door station camera.

- Slim 7" touchscreen indoor intercom monitor
- Connect to door stations and monitors via Ethernet
- MicroSD card slot (up to 32GB) for edge recording
- Integrates with most electronic sensors & alarms
- Dual-way bidirectional talk with echo suppression
- Receive visitor notifications, leave audio & video messages, remote view, remote unlock and 2-way talk via iOS & Android devices



7" Slimline Touchscreen Monitor



Connect & Power over Ethernet

Two-way talk & Remote Unlock

Apartment Indoor Monitor | Series Specifications

deneral denera	oduct Image ain Processor splay Size deo Compression arm Support ternal Capacity hernet / Network Jdio / 2-Way Talk directional Talk Jdio Enhancement	Image: Constraint of the second se
Central Centra	splay Size deo Compression arm Support ternal Capacity hernet / Network udio / 2-Way Talk directional Talk	7" Colour TFT LCD (800 x 480) Capacitive Touchscreen H.264 6 Input / 1 Output / 1 x RS485 MicroSD Slot, up to 32GB 1 x RJ45, 10/100Mbps Self-adaptive Omni-directional Microphone / Embedded Loudspeaker Support
General Genera	deo Compression arm Support ternal Capacity hernet / Network udio / 2-Way Talk directional Talk	H.264 6 Input / 1 Output / 1 x RS485 MicroSD Slot, up to 32GB 1 x RJ45, 10/100Mbps Self-adaptive Omni-directional Microphone / Embedded Loudspeaker Support
deneral General Audio Bic Au Au Au Au Au Au Bic Au Au Au Au Au Au Au Au Au Au Au Au Au	arm Support ternal Capacity hernet / Network udio / 2-Way Talk directional Talk	6 Input / 1 Output / 1 x R5485 MicroSD Slot, up to 32GB 1 x RJ45, 10/100Mbps Self-adaptive Omni-directional Microphone / Embedded Loudspeaker Support
Int Ett Au Bio Au Au Ins Ma Op Po	ternal Capacity hernet / Network udio / 2-Way Talk directional Talk	MicroSD Slot, up to 32GB 1 x RJ45, 10/100Mbps Self-adaptive Omni-directional Microphone / Embedded Loudspeaker Support
deneral Bic Au Au Au Au Au Au Op Op Op	hernet / Network udio / 2-Way Talk directional Talk	1 x RJ45, 10/100Mbps Self-adaptive Omni-directional Microphone / Embedded Loudspeaker Support
General General Au Au Au Au Au Au Au Au Au Au Au Au Au	udio / 2-Way Talk directional Talk	Omni-directional Microphone / Embedded Loudspeaker Support
General Genera	directional Talk	Support
Au Ins Ma Op Po		
Au Ins Ma Op Po	udio Enhancement	Supports echo suppression / DNR
Ins Ma Op Po		
Ma Op Po	udio Compression	G.711a, G.711Mu, G.711u, PCM
10	stallation	Surface Mount
10	aterial	PC + ABS Plastic
10	perating Temperature	-10 ~ +55℃ / 10 ~ 90%RH (max.)
We	ower Input / Use	12VDC, PoE (Requires INTIPMONPOE) / Operation <7W
	eight / Dimensions	0.80kg / 200 x 136 x 22mm
Installation bud	oduct Dimensions	

Example Installation

Apartment Outdoor Station


2 3 ^

SEV

4 9 2

* 0 # 4







Inline Power over Ethernet switch for IP intercoms that facilitates network and power for up to six IP intercom monitors. Simplify the expansion of intercom systems, save time and create professional installations with the INTIPMONPOE.

Your local VIP Vision[™] IP solutions professional:

PoE Switch

IP Intercom PoE Adapter