




Surveillance & deterrence.

Professional AI Series: Fixed AI turret dome with built-in strobe & siren in 5.0MP

Featuring smart motion detection, the Professional AI Series can distinguish between people, vehicles & other motion to filter out false alarms, providing real-time alerts and analytics. This model features intelligent people counting and active deterrence with a loud siren & strobe lights that activate in response to alarm or recorder events.

- Stream up to 5.0MP (2592 x 1944) at 20fps
- H.265+ encoding for efficient storage & streaming
- Strobe siren deterrence for alarm/recorder events
- MicroSD slot for recording at the edge up to 256GB
- Intelligent AI detection to identify people & vehicles
- Intelligent AI-enhanced people counting for retail capacity management and flow control
- Back/highlight compensation & true WDR (120dB)
- 3D digital noise reduction & auto white balance
- IP67 weather rated housing for outdoor use



Smart Person & Vehicle Detection





Built-in Siren & Strobe Alarm



People Counting & Flow Control

Specifications		5.0MP Fixed AI Turret Dome with Strobe & Siren	
Ordering Information		VSIPP-5DIRG-ID: Standard	
Camera	Image Sensor	1/2.7" 5.0MP Progressive Scan CMOS	
	Effective Pixels	2592 (H) x 1944 (V)	
	RAM / ROM	512MB / 128MB	
	Min Illumination	0.005 Lux/F1.0 (Color)	
	S/N Ratio	> 56dB	
	LED Illumination	1 x Infrared LED, 50m range, Auto/manual on/off control / 1 x Strobe LED	
	Lens	Lens / Iris	2.8mm F1.6 Fixed Lens
Field of View		Horizontal: 102°, Vertical: 71°	
Focus		Auto Focus / 0.9m Min. Focus Distance	
DORI	Detect (25px/m)	56m	
	Observe (63px/m)	22m	
	Recognise (125px/m)	11m	
	Identify (250px/m)	6m	
Video	Resolution	5.0MP (2592 x 1944) to CIF (352 x 288)	
	Frame Rate	Main	5.0MP (1 ~ 20fps) / 1080p (1 ~ 50fps)
		Sub	D1 (1 ~ 25fps)
		Third	1080p (1 ~ 17fps)
	Video Compression	H.265+ / H.265 / H.264+ / H.264 / H.264B / MJPEG	
	Bit Rate	H.265: 19 ~ 8192Kbps / H.264: 32 ~ 8192Kbps	
	Bit Rate Control	Constant bit rate (CBR) / Variable bit rate (VBR)	
	Day/Night	Auto (ICR) / Color / B&W	
	Lighting Compensation	BLC / HLC / WDR (120dB)	
	White Balance	Auto / Natural / Street Lamp / Outdoor / Manual	
Gain Control	Auto / Manual		
Noise Reduction	3D DNR		
Picture Control	Mirror / Flip (0°, 90°, 180°, 270°)		
IVS	Video Functions	Motion Detection (4 zones), Region of Interest (4 zones), Privacy Masking (4 zones), Smart Illumination, Defog, Object Abandoned / Missing, Heat Map Event Triggers: Motion Detection, Perimeter Protection, People Counting, Loitering Detection, Video Tampering, Scene Changing, Network Disconnection, IP Address Conflict, Illegal Access, Storage Anomaly	
	AI Functions	Perimeter Protection: People and vehicle detection using tripwire or intrusion rules People Counting: Supports people counting (Displays enter no., leave no. & pass no.), area people counting (Counts no. people or stay time / 4 rules configuration), Queue Management (Counts no. people or stay time / 4 rules configuration) Loitering detection: People gathering and parking detection	
	Intelligent search	Search people or vehicle detection events (Perimeter Protection)	
Network	Ethernet	RJ-45 (10/100Base-T)	
	Protocol	IPv4; IPv6; HTTP; HTTPS; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; PPPoE; 802.1x; SNMP	
	Streaming Method	Unicast / Multicast	
	Max. User Access	20 Users	
Interface	Video Interface	N/A	
	Audio Interface	Built-in Mic / Built-in Speaker / Audio Compression - G.711a; G.711Mu; G726; AAC, G723	
	Alarm Interface	1 channel in: 5mA 5VDC / 1 channel out: 300mA 12VDC	
	RS485	N/A	
	Edge Storage	MicroSD Card (up to 256GB) / NAS / FTP / SFTP	
Environmental	Interoperability	ONVIF (Profile S, Profile G, Profile T) / P2P / CGI / Milestone / Genetec	
	Power Supply	12VDC / PoE (802.3af)	
	Power Consumption	<7.2W	
	Operating Conditions	-40°C ~ +60°C / ≤95% RH	
	Ingress Protection	IP67	
	Vandal Resistance	N/A	
	Housing	Metal (Eyeball), Plastic (Case)	
	Pan/Tilt/Rotation	Pan: 0° ~ 360°, Tilt: 0° ~ 78°, Rotation: 0° ~ 360°	
	Dimensions	Ø122mm x 114mm	
	Net Weight	0.49kg	

Application



Junction Box		Wall Mount
VSBKTA130E		VSBKTB203W
Corner Mount	Pole Mount	Ceiling Mount
VSBKTB203W + VSBKTA151	VSBKTB203W + VSBKTA152E	VSBKTA106 + VSBKTB220C

Your local VIP Vision™ IP solutions professional: