





Completely wireless CCTV.

Watchguard™ Reolink 1080p wireless fixed lens bullet camera

The Watchguard[™] wireless bullet camera is a portable CCTV solution that can be installed anywhere, indoors and outdoors. Enjoy hassle free installations at any location with no wiring, WiFi or power adapter required.

- Stream up to Full HD / 1080p (1920 x 1080) at 15fps
- Fixed lens with wide 120° diagonal viewing angle
- 10m IR, capture details in low light conditions
- Two way talk with built-in microphone & speaker
- Smart PIR motion sensor, with up to 10m range
- IP65 rated weather resistant housing for outdoors
- Power via power supply (included) or solar panel
- View footage & receive alerts via the free Reolink app



Full HD Image Resolution



Weather Resistant Housing









Install Anywhere

100% wireless and portable, install in homes, offices and more



WiFi Connection

Easy setup & connection over the WiFi network



Solar Powered

Connect to the Reolink[™] solar panel for non stop power (Sold separately)



Remote View

Live view footage, 2 way talk, receive alerts & more via smartphone

Specifications		Watchguard™ Reolink 1080p Wireless Fixed Lens Bullet
Product Image		
Ordering Information		REO-AG3: Reolink Camera
Image Sensor		Starlight CMOS Image Sensor
Effective Pixels		1920 (H) x 1080 (V)
Infrared		6 x IR LEDs, 10m range
PIR Detection		Up to 10m (adjustable), 100° (H) PIR detecting angle
Lens / Iris		Fixed Lens (6x Digital Zoom)
Field of View		Diagonal: 120°
Focus		Fixed
Resolution		1080p / 2.0MP (1920 x 1080)
2	Main	1080p (1 ~ 15fps)
Frame Rate	Sub	N/A
	Third	N/A
Video Compr	ession	H.264
Operating Frequency		2.4GHz
Audio Interface		High quality speaker & microphone
Audio Alerts		Siren / Customised voice recordable alerts
Other Alerts		Instant email alerts and push notifications
Local Storage		Supports up to 64GB micro SD card
Cloud Storage		Supports Reolink Cloud
Battery		5200mAh rechargeable battery (Battery life varies based on settings, usage and temperature)
Solar DC Power Weather Resistance		Can be powered by Reolink solar panels
DC Power		Can be powered by 5V/2A power adapter
Weather Resistance		IP65
Operating Conditions		-10°C ~ 55°C
Dimensions		121mm x 90mm x 56mm
Net Weight		0.33kg (with battery)