FLASHVIEW



Purpose-built for 24/7 display.

Flashview LED LCD monitors available in 22 & 24 inches

Flashview LED LCD monitors are the monitor of choice for 24/7 continuous video displays, showing off video at Full HD 1080p resolution. With incredible digital processing with up to 16.7M colours for a vivid visual experience and fast response time for smooth operation with no blurring.

- Create impressive video displays in 1080p (22" & 24")
- Up to 1.07G colours for a realistic and vivid visuals
- Low response time for smooth operation
- VESA mountable (75x75 22", 100x100 24")
- Low energy consumption (<0.5W/<0.3W standby)
- Extra wide viewing angles 178° (H) x 178° (V)
- Audio output & built-in speakers (LCDFL22G only)
- VGA & HDMI video inputs



Full HD 1080p Resolution



Supports HDMI & VGA Inputs



Vibrant & Vivid Display Visuals



Series Specifications

Specifications		21.5" Full HD LED LCD Monitor	23.8" Full HD LED LCD Monitor	
Product Image				
Ordering Inform	nation	LCDFL22G	LCDFL24G	
Screen Size		21.5 inch	23.8 inch	
Aspect Ratio		16:9		
Resolution	olution 2.0MP / 1080p (1920 x 1080)		p (1920 x 1080)	
Display Panel		TN	IPS	
Brightness / Lu	minance	250	250cd/m ²	
Brightness / Lu Contrast Ratio		1000:1		
Display Colour		16.7M		
Viewing Angles		178° (H) / 178° (V)		
Response Time		6.5ms	14ms	
Refresh Rate		60Hz		
Inputs		1 x VGA, 1 x HDMI		
Outputs		1 x Audio		
Speakers		2 x 1.5W Speakers	N/A	
Power Input		12VDC, 2A	19VDC, 1.31A	
Power Consum	ption	24W (standard) / ≤0.5W (standby)	23W (standard) / ≤0.3W (standby)	
VESA		75 x 75mm	100 x 100mm	
Tilt		N/A		
Operating Tem	perature	0°C~40°C, <85%RH		
Dimensions (W	/D/H)	492 x 200 x 369mm (with stand) 492 x 38 x 285mm (without stand)	540 x 175 x 426mm (with stand) 540 x 39 x 321mm (without stand)	
Net Weight		2.1kg	2.7kg	
Included Acces	sories	HDMI cable, power adapter, stand		
Product Diagra	ms	26 26 26 26 26 26 26 26 26 26 26 26 26 2		

Your local Flashview professional: