



## **Elegant access solutions.**

## Residential Series: IP intercom door station with 2.0MP camera

This Residential Series video intercom door stations is single channel, ideal for homes & single-premises buildings. The door stations features a 2.0MP camera with auto day/night IRC, all in a stylish aluminium body.

- 1/2.5" 2.0MP 1.95mm lens camera with 169° FOV •
- Built-in microphone and speaker for 2-way talk •
- Connect with intercom monitor(s) via Ethernet •
- Intuitive, easy-to-use interface

- Alarm and RS485 input/output relays
- Connect & power via 2-wire or Power over Ethernet •
- Weather & vandal resistant IP55/IK07 aluminium body
- · Flush and surface mount installation options



**Remote Access & Answer via App** 

## **Residential Door Station** | Series Specifications

	Model	INTIPRDSG3
	model	
	Product Image	e e a
	Main Processor	Embedded Microprocessor
	Camera System	1/2.5" 2.0 Megapixel CMOS with 1.9mm lens (Horizontal FoV: 169°)
ial	Low-Light Application	Day/Night ICR
General	Card Support	N/A
0	Keypad	1 Mechanical Button
	Tamper Detection	Yes 1 x alarm input / 1 x alarm output / 1 x RS485
	Input / Output Audio / 2-Way Talk	Omni-directional Microphone & Embedded Loudspeaker for 2-way talk
	Internal MicroSD Slot	Yes, up to 64GB
	Ethernet / Network	10M/100Mbps Self-adaptive / TCP/IP protocol
	Max. Additional Door Stations	20
	Max. Indoor Monitors	10
	App Connection	QR Code
	Vandal Resistant	IK07
٩	Ingress Protection	IP55
Environmental	Installation Options	Supports surface box and flush box mount
nuc	Construction	Aluminium
vir	Installation Kit	N/A
ш	Power Input	48VDC 1A, PoE (802.3af)
	Weight / Dimensions	0.35kg / 130 x 96 x 29mm
Accessories	Product Diagram	
	Mounting Options	Flush Box Mount (INTIPRDSG-FB) / Surface Box Mount (INTIPADSG-SB)
		Flush Box Mount (INTIPRUSG-FB) / Surface Box Mount (INTIPRUSG-SB)

Your local VIP Vision<sup>™</sup> IP solutions professional: